# Isolated DC/DC Converter

Wechat

Whatsapp

Your Global Partner for Power Supply Solution Services in China.
Your unique project needs , we provide customized services


**GUANGZHOU IDEALPLUSING INFORMATION TECHNOLOGY CO., LTD**

Website: www.idealplusing.com www. idealpowersupply.com

Office ADD: NO.38 Gaopu Road, Tianhe, Guangzhou, Guangdong Province, China. 510520.

Factory #1 ADD: 7/F, Block A, Cabo Tec. park, North of HuaFa Road, Gongming, Guangming new Dis. ,SZ,China.

Factory #2 ADD: 3/F, Building C, HengTongFa Industrial Area, TangTou Industrial Park, ShiYan , Baoan , SZ, China.

Tel: +86-20-89282095 Mobile & Whatsapp: +86-18928830209 EMAIL: info@idealplusing.com

# DATASHEET

| Name | Isolated DC DC Converter | | Model | IPS-DTD20-284S350-7.1 | | |
|---|---|---|---|---|---|---|
| Product Size | 285*133*75 MM | | Design | Input and output are completely isolated | | |
| Net Weight | 4KG | | Gross Weight | 5KG | | |
| **Technical Parameters** | **Minimum** | **Typical Value** | **Maximum** | **Unit** | **Condition** | **Remark** |
| Input voltage range | 20 | 24 | 28 | VDC | | |
| Output voltage | | 350 | | VDC | | |
| Output current | | 7.1 | | A | | |
| Voltage regulation | | ±1 | | % | | |
| Load regulation | | ±1 | | % | | |
| Ripple and noise | | 200 | | Mvp-p | | |
| **General Features** | | | | | | |
| Insulation withstand voltage | | 1050 | | VDC | Input to housing | |
| Insulation withstand voltage | | 500 | | VDC | Output to housing | |
| Isolation voltage | | 1500 | | VDC | Input to output | |
| Insulation impedance | | 200 | | MΩ | | |
| Protection function | Input undervoltage, over-temperature protection, output overcurrent, short circuit protection | | | | | |
| **Environmental characteristics** | | | | | | |
| Operating temperature | -25 | | 85 | ℃ | | |
| Storage temperature | -45 | | 105 | ℃ | | |
| Waterproof grade | | / | | | No waterproof | |
| Cooling method | | Air Cooling | | | | |
| Output method | | Terminal Blocks | | | | |
| Remark | | | | | | |
| Reference Picture ONLY | | | | | | |

Remark: All the above parameters are theoretical values, please refer to the actual product testing data for actual products.

We specialize in customizing DC-DC converters to meet your specific requirements.
With customized input and output voltage and current, our offerings range from 1VDC to 2000VDC DC and 1A to 1000A.
We provide both isolated and non-isolated converter design options.
Please visit our website and submit any inquiries to explore our capabilities further.

If you can not find the right specification to meet your requirement.
Contact us now! It will not cost you one cent when you ask us anything, but it may be a chance for both of us!
Our dedicated team endeavors to respond within one hour.

Thank you for considering our services.

# Catalogue

Reference Images.....4

100W 24VDC-350VDC INPUT.....11

150W 24VDC-400VDC INPUT.....15

200W 12VDC-400VDC INPUT.....19

250W 12VDC-400VDC INPUT.....25

300W 12VDC-400VDC INPUT.....29

350W 12VDC-400VDC INPUT.....33

400W 12VDC-400VDC INPUT.....38

500W 12VDC-600VDC INPUT.....42

600W 12VDC-600VDC INPUT.....49

750W 12VDC-600VDC INPUT.....56

1000W 12VDC-600VDC INPUT.....63

1500W 12VDC-400VDC INPUT.....70

2000W 12VDC-400VDC INPUT.....76

3000W 12VDC-400VDC INPUT.....81

4000W 24VDC-500VDC INPUT.....87

5000W 12VDC-500VDC INPUT.....94

6000W 24VDC-500VDC INPUT.....100

7500W 36VDC-500VDC INPUT.....107

# 199-110-50 MM

# 240-124-65 MM

## 260-160-85 MM

## 312-190-95 MM

# 260-132-68 MM

# 292-132-68 MM

# 440*300*110 MM





IDEALPLUSING®

IDEALPLUSING®

IDEALPLUSING®



IDEALPLUSING®



| 100W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 3 | 24VDC±15% | 24VDC±1-2% | 4.18A | 3.33A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 4 | 24VDC±15% | 36VDC±1-2% | 2.78A | 2.22A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 5 | 24VDC±15% | 48VDC±1-2% | 2.08A | 1.67A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 6 | 24VDC±15% | 64VDC±1-2% | 1.56A | 1.25A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 7 | 24VDC±15% | 100VDC±1-2% | 1.0A | 0.8A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 8 | 24VDC±15% | 150VDC±1-2% | 0.67A | 0.53A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 9 | 24VDC±15% | 200VDC±1-2% | 0.5A | 0.4A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 10 | 24VDC±15% | 220VDC±1-2% | 0.45A | 0.36A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 11 | 24VDC±15% | 250VDC±1-2% | 0.4A | 0.32A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 12 | 24VDC±15% | 280VDC±1-2% | 0.36A | 0.286A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 13 | 24VDC±15% | 300VDC±1-2% | 0.33A | 0.267A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 14 | 24VDC±15% | 350VDC±1-2% | 0.28A | 0.228A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 100W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 17 | 36VDC±15% | 24VDC±1-2% | 4.18A | 3.33A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 18 | 36VDC±15% | 36VDC±1-2% | 2.78A | 2.22A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 19 | 36VDC±15% | 48VDC±1-2% | 2.08A | 1.67A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 20 | 36VDC±15% | 64VDC±1-2% | 1.56A | 1.25A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 21 | 36VDC±15% | 100VDC±1-2% | 1.0A | 0.8A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 22 | 36VDC±15% | 150VDC±1-2% | 0.67A | 0.53A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 23 | 36VDC±15% | 200VDC±1-2% | 0.5A | 0.4A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 24 | 36VDC±15% | 220VDC±1-2% | 0.45A | 0.36A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 25 | 36VDC±15% | 250VDC±1-2% | 0.4A | 0.32A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 26 | 36VDC±15% | 280VDC±1-2% | 0.36A | 0.286A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 27 | 36VDC±15% | 300VDC±1-2% | 0.33A | 0.267A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 28 | 36VDC±15% | 350VDC±1-2% | 0.28A | 0.228A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 100W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 31 | 48VDC±15% | 24VDC±1-2% | 4.18A | 3.33A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 32 | 48VDC±15% | 36VDC±1-2% | 2.78A | 2.22A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 33 | 48VDC±15% | 48VDC±1-2% | 2.08A | 1.67A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 34 | 48VDC±15% | 64VDC±1-2% | 1.56A | 1.25A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 35 | 48VDC±15% | 100VDC±1-2% | 1.0A | 0.8A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 36 | 48VDC±15% | 150VDC±1-2% | 0.67A | 0.53A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 37 | 48VDC±15% | 200VDC±1-2% | 0.5A | 0.4A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 38 | 48VDC±15% | 220VDC±1-2% | 0.45A | 0.36A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 39 | 48VDC±15% | 250VDC±1-2% | 0.4A | 0.32A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 40 | 48VDC±15% | 280VDC±1-2% | 0.36A | 0.286A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 41 | 48VDC±15% | 300VDC±1-2% | 0.33A | 0.267A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 42 | 48VDC±15% | 350VDC±1-2% | 0.28A | 0.228A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |

| 100W 64VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 45 | 64VDC±15% | 24VDC±1-2% | 4.18A | 3.33A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 46 | 64VDC±15% | 36VDC±1-2% | 2.78A | 2.22A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 47 | 64VDC±15% | 48VDC±1-2% | 2.08A | 1.67A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 48 | 64VDC±15% | 64VDC±1-2% | 1.56A | 1.25A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 49 | 64VDC±15% | 100VDC±1-2% | 1.0A | 0.8A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 50 | 64VDC±15% | 150VDC±1-2% | 0.67A | 0.53A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 51 | 64VDC±15% | 200VDC±1-2% | 0.5A | 0.4A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 52 | 64VDC±15% | 220VDC±1-2% | 0.45A | 0.36A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 53 | 64VDC±15% | 250VDC±1-2% | 0.4A | 0.32A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 54 | 64VDC±15% | 280VDC±1-2% | 0.36A | 0.286A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 55 | 64VDC±15% | 300VDC±1-2% | 0.33A | 0.267A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 56 | 64VDC±15% | 350VDC±1-2% | 0.28A | 0.228A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 100W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 59 | 100VDC±15% | 24VDC±1-2% | 4.18A | 3.33A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 60 | 100VDC±15% | 36VDC±1-2% | 2.78A | 2.22A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 61 | 100VDC±15% | 48VDC±1-2% | 2.08A | 1.67A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 62 | 100VDC±15% | 64VDC±1-2% | 1.56A | 1.25A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 63 | 100VDC±15% | 100VDC±1-2% | 1.0A | 0.8A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 64 | 100VDC±15% | 150VDC±1-2% | 0.67A | 0.53A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 65 | 100VDC±15% | 200VDC±1-2% | 0.5A | 0.4A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 66 | 100VDC±15% | 220VDC±1-2% | 0.45A | 0.36A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 67 | 100VDC±15% | 250VDC±1-2% | 0.4A | 0.32A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 68 | 100VDC±15% | 280VDC±1-2% | 0.36A | 0.286A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 69 | 100VDC±15% | 300VDC±1-2% | 0.33A | 0.267A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 70 | 100VDC±15% | 350VDC±1-2% | 0.28A | 0.228A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 100W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 73 | 150VDC±15% | 24VDC±1-2% | 4.18A | 3.33A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 74 | 150VDC±15% | 36VDC±1-2% | 2.78A | 2.22A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 75 | 150VDC±15% | 48VDC±1-2% | 2.08A | 1.67A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 76 | 150VDC±15% | 64VDC±1-2% | 1.56A | 1.25A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 77 | 150VDC±15% | 100VDC±1-2% | 1.0A | 0.8A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 78 | 150VDC±15% | 150VDC±1-2% | 0.67A | 0.53A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 79 | 150VDC±15% | 200VDC±1-2% | 0.5A | 0.4A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 80 | 150VDC±15% | 220VDC±1-2% | 0.45A | 0.36A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 81 | 150VDC±15% | 250VDC±1-2% | 0.4A | 0.32A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 82 | 150VDC±15% | 280VDC±1-2% | 0.36A | 0.286A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 83 | 150VDC±15% | 300VDC±1-2% | 0.33A | 0.267A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 84 | 150VDC±15% | 350VDC±1-2% | 0.28A | 0.228A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |

| 100W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 87 | 200VDC±15% | 24VDC±1-2% | 4.18A | 3.33A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 88 | 200VDC±15% | 36VDC±1-2% | 2.78A | 2.22A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 89 | 200VDC±15% | 48VDC±1-2% | 2.08A | 1.67A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 90 | 200VDC±15% | 64VDC±1-2% | 1.56A | 1.25A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 91 | 200VDC±15% | 100VDC±1-2% | 1.0A | 0.8A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 92 | 200VDC±15% | 150VDC±1-2% | 0.67A | 0.53A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 93 | 200VDC±15% | 200VDC±1-2% | 0.5A | 0.4A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 94 | 200VDC±15% | 220VDC±1-2% | 0.45A | 0.36A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 95 | 200VDC±15% | 250VDC±1-2% | 0.4A | 0.32A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 96 | 200VDC±15% | 280VDC±1-2% | 0.36A | 0.286A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 97 | 200VDC±15% | 300VDC±1-2% | 0.33A | 0.267A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 98 | 200VDC±15% | 350VDC±1-2% | 0.28A | 0.228A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 100W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 101 | 220VDC±15% | 24VDC±1-2% | 4.18A | 3.33A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 102 | 220VDC±15% | 36VDC±1-2% | 2.78A | 2.22A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 103 | 220VDC±15% | 48VDC±1-2% | 2.08A | 1.67A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 104 | 220VDC±15% | 64VDC±1-2% | 1.56A | 1.25A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 105 | 220VDC±15% | 100VDC±1-2% | 1.0A | 0.8A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 106 | 220VDC±15% | 150VDC±1-2% | 0.67A | 0.53A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 107 | 220VDC±15% | 200VDC±1-2% | 0.5A | 0.4A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 108 | 220VDC±15% | 220VDC±1-2% | 0.45A | 0.36A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 109 | 220VDC±15% | 250VDC±1-2% | 0.4A | 0.32A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 110 | 220VDC±15% | 280VDC±1-2% | 0.36A | 0.286A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 111 | 220VDC±15% | 300VDC±1-2% | 0.33A | 0.267A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 112 | 220VDC±15% | 350VDC±1-2% | 0.28A | 0.228A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 100W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 115 | 250VDC±15% | 24VDC±1-2% | 4.18A | 3.33A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 116 | 250VDC±15% | 36VDC±1-2% | 2.78A | 2.22A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 117 | 250VDC±15% | 48VDC±1-2% | 2.08A | 1.67A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 118 | 250VDC±15% | 64VDC±1-2% | 1.56A | 1.25A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 119 | 250VDC±15% | 100VDC±1-2% | 1.0A | 0.8A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 120 | 250VDC±15% | 150VDC±1-2% | 0.67A | 0.53A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 121 | 250VDC±15% | 200VDC±1-2% | 0.5A | 0.4A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 122 | 250VDC±15% | 220VDC±1-2% | 0.45A | 0.36A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 123 | 250VDC±15% | 250VDC±1-2% | 0.4A | 0.32A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 124 | 250VDC±15% | 280VDC±1-2% | 0.36A | 0.286A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 125 | 250VDC±15% | 300VDC±1-2% | 0.33A | 0.267A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 126 | 250VDC±15% | 350VDC±1-2% | 0.28A | 0.228A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |

| 100W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 129 | 280VDC±15% | 24VDC±1-2% | 4.18A | 3.33A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 130 | 280VDC±15% | 36VDC±1-2% | 2.78A | 2.22A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 131 | 280VDC±15% | 48VDC±1-2% | 2.08A | 1.67A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 132 | 280VDC±15% | 64VDC±1-2% | 1.56A | 1.25A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 133 | 280VDC±15% | 100VDC±1-2% | 1.0A | 0.8A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 134 | 280VDC±15% | 150VDC±1-2% | 0.67A | 0.53A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 135 | 280VDC±15% | 200VDC±1-2% | 0.5A | 0.4A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 136 | 280VDC±15% | 220VDC±1-2% | 0.45A | 0.36A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 137 | 280VDC±15% | 250VDC±1-2% | 0.4A | 0.32A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 138 | 280VDC±15% | 280VDC±1-2% | 0.36A | 0.286A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 139 | 280VDC±15% | 300VDC±1-2% | 0.33A | 0.267A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 140 | 280VDC±15% | 350VDC±1-2% | 0.28A | 0.228A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 100W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 143 | 300VDC±15% | 24VDC±1-2% | 4.18A | 3.33A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 144 | 300VDC±15% | 36VDC±1-2% | 2.78A | 2.22A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 145 | 300VDC±15% | 48VDC±1-2% | 2.08A | 1.67A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 146 | 300VDC±15% | 64VDC±1-2% | 1.56A | 1.25A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 147 | 300VDC±15% | 100VDC±1-2% | 1.0A | 0.8A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 148 | 300VDC±15% | 150VDC±1-2% | 0.67A | 0.53A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 149 | 300VDC±15% | 200VDC±1-2% | 0.5A | 0.4A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 150 | 300VDC±15% | 220VDC±1-2% | 0.45A | 0.36A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 151 | 300VDC±15% | 250VDC±1-2% | 0.4A | 0.32A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 152 | 300VDC±15% | 280VDC±1-2% | 0.36A | 0.286A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 153 | 300VDC±15% | 300VDC±1-2% | 0.33A | 0.267A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 154 | 300VDC±15% | 350VDC±1-2% | 0.28A | 0.228A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 100W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 157 | 350VDC±15% | 24VDC±1-2% | 4.18A | 3.33A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 158 | 350VDC±15% | 36VDC±1-2% | 2.78A | 2.22A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 159 | 350VDC±15% | 48VDC±1-2% | 2.08A | 1.67A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 160 | 350VDC±15% | 64VDC±1-2% | 1.56A | 1.25A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 161 | 350VDC±15% | 100VDC±1-2% | 1.0A | 0.8A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 162 | 350VDC±15% | 150VDC±1-2% | 0.67A | 0.53A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 163 | 350VDC±15% | 200VDC±1-2% | 0.5A | 0.4A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 164 | 350VDC±15% | 220VDC±1-2% | 0.45A | 0.36A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 165 | 350VDC±15% | 250VDC±1-2% | 0.4A | 0.32A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 166 | 350VDC±15% | 280VDC±1-2% | 0.36A | 0.286A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 167 | 350VDC±15% | 300VDC±1-2% | 0.33A | 0.267A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |
| 168 | 350VDC±15% | 350VDC±1-2% | 0.28A | 0.228A | 100W | 80W | 159*98*38MM | 0.5KG/0.8KG |

| 150W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| **171** | 24VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 172 | 24VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 173 | 24VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 174 | 24VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 175 | 24VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 176 | 24VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 177 | 24VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 178 | 24VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 179 | 24VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 180 | 24VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 181 | 24VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 182 | 24VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 183 | 24VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 150W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 186 | 36VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 187 | 36VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 188 | 36VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 189 | 36VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 190 | 36VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 191 | 36VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 192 | 36VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 193 | 36VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 194 | 36VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 195 | 36VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 196 | 36VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 197 | 36VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 198 | 36VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 150W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 201 | 48VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 202 | 48VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 203 | 48VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 204 | 48VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 205 | 48VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 206 | 48VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 207 | 48VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 208 | 48VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 209 | 48VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 210 | 48VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 211 | 48VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 212 | 48VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 213 | 48VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |

| 150W 64VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 216 | 64VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 217 | 64VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 218 | 64VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 219 | 64VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 220 | 64VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 221 | 64VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 222 | 64VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 223 | 64VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 224 | 64VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 225 | 64VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 226 | 64VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 227 | 64VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 228 | 64VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 150W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 231 | 100VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 232 | 100VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 233 | 100VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 234 | 100VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 235 | 100VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 236 | 100VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 237 | 100VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 238 | 100VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 239 | 100VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 240 | 100VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 241 | 100VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 242 | 100VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 243 | 100VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 150W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 246 | 150VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 247 | 150VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 248 | 150VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 249 | 150VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 250 | 150VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 251 | 150VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 252 | 150VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 253 | 150VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 254 | 150VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 255 | 150VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 256 | 150VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 257 | 150VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 258 | 150VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |

| 150W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 261 | 200VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 262 | 200VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 263 | 200VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 264 | 200VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 265 | 200VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 266 | 200VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 267 | 200VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 268 | 200VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 269 | 200VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 270 | 200VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 271 | 200VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 272 | 200VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 273 | 200VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 150W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 276 | 220VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 277 | 220VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 278 | 220VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 279 | 220VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 280 | 220VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 281 | 220VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 282 | 220VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 283 | 220VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 284 | 220VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 285 | 220VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 286 | 220VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 287 | 220VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 288 | 220VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 150W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 291 | 250VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 292 | 250VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 293 | 250VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 294 | 250VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 295 | 250VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 296 | 250VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 297 | 250VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 298 | 250VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 299 | 250VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 300 | 250VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 301 | 250VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 302 | 250VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 303 | 250VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |

| 150W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 306 | 280VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 307 | 280VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 308 | 280VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 309 | 280VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 310 | 280VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 311 | 280VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 312 | 280VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 313 | 280VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 314 | 280VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 315 | 280VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 316 | 280VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 317 | 280VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 318 | 280VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 150W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 321 | 300VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 322 | 300VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 323 | 300VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 324 | 300VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 325 | 300VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 326 | 300VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 327 | 300VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 328 | 300VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 329 | 300VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 330 | 300VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 331 | 300VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 332 | 300VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 333 | 300VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 150W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 336 | 350VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 337 | 350VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 338 | 350VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 339 | 350VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 340 | 350VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 341 | 350VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 342 | 350VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 343 | 350VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 344 | 350VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 345 | 350VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 346 | 350VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 347 | 350VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 348 | 350VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |

# 150W 400VDC/ 200W 12VDC-24VDC

| 150W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 351 | 400VDC±15% | 24VDC±1-2% | 6.2A | 5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 352 | 400VDC±15% | 36VDC±1-2% | 4.1A | 3.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 353 | 400VDC±15% | 48VDC±1-2% | 3.1A | 2.5A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 354 | 400VDC±15% | 64VDC±1-2% | 2.3A | 1.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 355 | 400VDC±15% | 100VDC±1-2% | 1.5A | 1.2A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 356 | 400VDC±15% | 150VDC±1-2% | 1A | 0.8A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 357 | 400VDC±15% | 200VDC±1-2% | 0.75A | 0.6A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 358 | 400VDC±15% | 220VDC±1-2% | 0.68A | 0.54A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 359 | 400VDC±15% | 250VDC±1-2% | 0.6A | 0.48A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 360 | 400VDC±15% | 280VDC±1-2% | 0.53A | 0.42A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 361 | 400VDC±15% | 300VDC±1-2% | 0.5A | 0.4A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 362 | 400VDC±15% | 350VDC±1-2% | 0.42A | 0.34A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 363 | 400VDC±15% | 400VDC±1-2% | 0.375A | 0.3A | 150W | 120W | 159*98*38MM | 0.5KG/0.8KG |
| 200W 12VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 366 | 12VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 367 | 12VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 368 | 12VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 369 | 12VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 370 | 12VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 371 | 12VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 372 | 12VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 373 | 12VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 374 | 12VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 375 | 12VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 376 | 12VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 377 | 12VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 378 | 12VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 379 | 12VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 200W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 382 | 24VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 383 | 24VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 384 | 24VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 385 | 24VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 386 | 24VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 387 | 24VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 388 | 24VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 389 | 24VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 390 | 24VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 391 | 24VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 392 | 24VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 393 | 24VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 394 | 24VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 395 | 24VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |

# 200W 36VDC-64VDC

| 200W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 398 | 36VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 399 | 36VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 400 | 36VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 401 | 36VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 402 | 36VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 403 | 36VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 404 | 36VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 405 | 36VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 406 | 36VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 407 | 36VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 408 | 36VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 409 | 36VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 410 | 36VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 411 | 36VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 200W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 414 | 48VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 415 | 48VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 416 | 48VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 417 | 48VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 418 | 48VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 419 | 48VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 420 | 48VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 421 | 48VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 422 | 48VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 423 | 48VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 424 | 48VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 425 | 48VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 426 | 48VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 427 | 48VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 200W 64VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 430 | 64VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 431 | 64VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 432 | 64VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 433 | 64VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 434 | 64VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 435 | 64VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 436 | 64VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 437 | 64VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 438 | 64VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 439 | 64VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 440 | 64VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 441 | 64VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 442 | 64VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 443 | 64VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |

# 200W 100VDC-200VDC

| 200W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 446 | 100VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 447 | 100VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 448 | 100VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 449 | 100VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 450 | 100VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 451 | 100VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 452 | 100VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 453 | 100VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 454 | 100VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 455 | 100VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 456 | 100VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 457 | 100VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 458 | 100VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 459 | 100VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 200W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 462 | 150VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 463 | 150VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 464 | 150VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 465 | 150VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 466 | 150VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 467 | 150VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 468 | 150VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 469 | 150VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 470 | 150VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 471 | 150VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 472 | 150VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 473 | 150VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 474 | 150VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 475 | 150VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 200W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 478 | 200VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 479 | 200VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 480 | 200VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 481 | 200VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 482 | 200VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 483 | 200VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 484 | 200VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 485 | 200VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 486 | 200VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 487 | 200VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 488 | 200VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 489 | 200VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 490 | 200VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 491 | 200VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |

# 200W 220VDC-280VDC

| 200W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 494 | 220VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 495 | 220VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 496 | 220VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 497 | 220VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 498 | 220VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 499 | 220VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 500 | 220VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 501 | 220VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 502 | 220VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 503 | 220VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 504 | 220VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 505 | 220VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 506 | 220VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 507 | 220VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 200W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 510 | 250VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 511 | 250VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 512 | 250VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 513 | 250VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 514 | 250VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 515 | 250VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 516 | 250VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 517 | 250VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 518 | 250VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 519 | 250VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 520 | 250VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 521 | 250VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 522 | 250VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 523 | 250VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 200W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 526 | 280VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 527 | 280VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 528 | 280VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 529 | 280VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 530 | 280VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 531 | 280VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 532 | 280VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 533 | 280VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 534 | 280VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 535 | 280VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 536 | 280VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 537 | 280VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 538 | 280VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 539 | 280VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |

| 200W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 542 | 300VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 543 | 300VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 544 | 300VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 545 | 300VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 546 | 300VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 547 | 300VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 548 | 300VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 549 | 300VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 550 | 300VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 551 | 300VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 552 | 300VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 553 | 300VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 554 | 300VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 555 | 300VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 200W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 558 | 350VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 559 | 350VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 560 | 350VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 561 | 350VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 562 | 350VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 563 | 350VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 564 | 350VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 565 | 350VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 566 | 350VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 567 | 350VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 568 | 350VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 569 | 350VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 570 | 350VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 571 | 350VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 200W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 574 | 400VDC±15% | 12VDC±1-2% | 16.6A | 13.3A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 575 | 400VDC±15% | 24VDC±1-2% | 8.32A | 6.66A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 576 | 400VDC±15% | 36VDC±1-2% | 5.56A | 4.44A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 577 | 400VDC±15% | 48VDC±1-2% | 4.16A | 3.33A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 578 | 400VDC±15% | 64VDC±1-2% | 3.12A | 2.5A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 579 | 400VDC±15% | 100VDC±1-2% | 2A | 1.6A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 580 | 400VDC±15% | 150VDC±1-2% | 1.34A | 1.06A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 581 | 400VDC±15% | 200VDC±1-2% | 1A | 0.8A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 582 | 400VDC±15% | 220VDC±1-2% | 0.9A | 0.72A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 583 | 400VDC±15% | 250VDC±1-2% | 0.8A | 0.64A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 584 | 400VDC±15% | 280VDC±1-2% | 0.72A | 0.57A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 585 | 400VDC±15% | 300VDC±1-2% | 0.66A | 0.53A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 586 | 400VDC±15% | 350VDC±1-2% | 0.56A | 0.45A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |
| 587 | 400VDC±15% | 400VDC±1-2% | 0.5A | 0.4A | 200W | 160W | 199*110*50MM | 0.8KG/1KG |

| 250W 12VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 590 | 12VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 591 | 12VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 592 | 12VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 593 | 12VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 594 | 12VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 595 | 12VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 596 | 12VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 597 | 12VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 598 | 12VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 599 | 12VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 600 | 12VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 601 | 12VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 602 | 12VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 603 | 12VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 250W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 606 | 24VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 607 | 24VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 608 | 24VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 609 | 24VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 610 | 24VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 611 | 24VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 612 | 24VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 613 | 24VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 614 | 24VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 615 | 24VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 616 | 24VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 617 | 24VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 618 | 24VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 619 | 24VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |

| 250W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 622 | 36VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 623 | 36VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 624 | 36VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 625 | 36VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 626 | 36VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 627 | 36VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 628 | 36VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 629 | 36VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 630 | 36VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 631 | 36VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 632 | 36VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 633 | 36VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 634 | 36VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 635 | 36VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 250W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 638 | 48VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 639 | 48VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 640 | 48VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 641 | 48VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 642 | 48VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 643 | 48VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 644 | 48VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 645 | 48VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 646 | 48VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 647 | 48VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 648 | 48VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 649 | 48VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 650 | 48VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 651 | 48VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 250W 64VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 654 | 64VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 655 | 64VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 656 | 64VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 657 | 64VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 658 | 64VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 659 | 64VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 660 | 64VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 661 | 64VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 662 | 64VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 663 | 64VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 664 | 64VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 665 | 64VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 666 | 64VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 667 | 64VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |

# 250W 100VDC-200VDC

| 250W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 670 | 100VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 671 | 100VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 672 | 100VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 673 | 100VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 674 | 100VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 675 | 100VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 676 | 100VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 677 | 100VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 678 | 100VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 679 | 100VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 680 | 100VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 681 | 100VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 682 | 100VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 683 | 100VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 250W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 686 | 150VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 687 | 150VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 688 | 150VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 689 | 150VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 690 | 150VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 691 | 150VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 692 | 150VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 693 | 150VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 694 | 150VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 695 | 150VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 696 | 150VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 697 | 150VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 698 | 150VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 699 | 150VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 250W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 702 | 200VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 703 | 200VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 704 | 200VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 705 | 200VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 706 | 200VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 707 | 200VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 708 | 200VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 709 | 200VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 710 | 200VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 711 | 200VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 712 | 200VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 713 | 200VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 714 | 200VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 715 | 200VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |

# 250W 220VDC-240VDC

| 250W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 718 | 220VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 719 | 220VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 720 | 220VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 721 | 220VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 722 | 220VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 723 | 220VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 724 | 220VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 725 | 220VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 726 | 220VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 727 | 220VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 728 | 220VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 729 | 220VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 730 | 220VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 731 | 220VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 250W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 734 | 250VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 735 | 250VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 736 | 250VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 737 | 250VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 738 | 250VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 739 | 250VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 740 | 250VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 741 | 250VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 742 | 250VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 743 | 250VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 744 | 250VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 745 | 250VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 746 | 250VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 747 | 250VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 250W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 750 | 280VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 751 | 280VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 752 | 280VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 753 | 280VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 754 | 280VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 755 | 280VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 756 | 280VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 757 | 280VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 758 | 280VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 759 | 280VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 760 | 280VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 761 | 280VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 762 | 280VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 763 | 280VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |

# 250W 300VDC-400VDC

| 250W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 766 | 300VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 767 | 300VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 768 | 300VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 769 | 300VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 770 | 300VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 771 | 300VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 772 | 300VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 773 | 300VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 774 | 300VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 775 | 300VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 776 | 300VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 777 | 300VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 778 | 300VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 779 | 300VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 250W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 782 | 350VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 783 | 350VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 784 | 350VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 785 | 350VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 786 | 350VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 787 | 350VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 788 | 350VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 789 | 350VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 790 | 350VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 791 | 350VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 792 | 350VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 793 | 350VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 794 | 350VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 795 | 350VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 250W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 798 | 400VDC±15% | 12VDC±1-2% | 20.8A | 16.6A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 799 | 400VDC±15% | 24VDC±1-2% | 10.4A | 8.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 800 | 400VDC±15% | 36VDC±1-2% | 6.9A | 5.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 801 | 400VDC±15% | 48VDC±1-2% | 5.2A | 4.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 802 | 400VDC±15% | 64VDC±1-2% | 3.9A | 3.1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 803 | 400VDC±15% | 100VDC±1-2% | 2.5A | 2A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 804 | 400VDC±15% | 150VDC±1-2% | 1.6A | 1.3A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 805 | 400VDC±15% | 200VDC±1-2% | 1.25A | 1A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 806 | 400VDC±15% | 220VDC±1-2% | 1.1A | 0.9A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 807 | 400VDC±15% | 250VDC±1-2% | 1A | 0.88A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 808 | 400VDC±15% | 280VDC±1-2% | 0.89A | 0.78A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 809 | 400VDC±15% | 300VDC±1-2% | 0.83A | 0.66A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 810 | 400VDC±15% | 350VDC±1-2% | 0.71A | 0.57A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |
| 811 | 400VDC±15% | 400VDC±1-2% | 0.625A | 0.5A | 250W | 200W | 199*110*50MM | 0.8KG/1KG |

| 300W 12VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 814 | 12VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 815 | 12VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 816 | 12VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 817 | 12VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 818 | 12VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 819 | 12VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 820 | 12VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 821 | 12VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 822 | 12VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 823 | 12VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 824 | 12VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 825 | 12VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 826 | 12VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 827 | 12VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 300W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 830 | 24VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 831 | 24VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 832 | 24VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 833 | 24VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 834 | 24VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 835 | 24VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 836 | 24VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 837 | 24VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 838 | 24VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 839 | 24VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 840 | 24VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 841 | 24VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 842 | 24VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 843 | 24VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 300W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 846 | 36VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 847 | 36VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 848 | 36VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 849 | 36VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 850 | 36VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 851 | 36VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 852 | 36VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 853 | 36VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 854 | 36VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 855 | 36VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 856 | 36VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 857 | 36VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 858 | 36VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 859 | 36VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |

# 300W 48VDC-100VDC

| 300W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 862 | 48VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 863 | 48VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 864 | 48VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 865 | 48VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 866 | 48VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 867 | 48VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 868 | 48VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 869 | 48VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 870 | 48VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 871 | 48VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 872 | 48VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 873 | 48VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 874 | 48VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 875 | 48VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 300W 64VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 878 | 64VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 879 | 64VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 880 | 64VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 881 | 64VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 882 | 64VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 883 | 64VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 884 | 64VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 885 | 64VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 886 | 64VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 887 | 64VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 888 | 64VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 889 | 64VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 890 | 64VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 891 | 64VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 300W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 894 | 100VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 895 | 100VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 896 | 100VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 897 | 100VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 898 | 100VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 899 | 100VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 900 | 100VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 901 | 100VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 902 | 100VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 903 | 100VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 904 | 100VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 905 | 100VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 906 | 100VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 907 | 100VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |

# 300W 150VDC-220VDC

| 300W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 910 | 150VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 911 | 150VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 912 | 150VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 913 | 150VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 914 | 150VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 915 | 150VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 916 | 150VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 917 | 150VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 918 | 150VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 919 | 150VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 920 | 150VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 921 | 150VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 922 | 150VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 923 | 150VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 300W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 926 | 200VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 927 | 200VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 928 | 200VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 929 | 200VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 930 | 200VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 931 | 200VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 932 | 200VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 933 | 200VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 934 | 200VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 935 | 200VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 936 | 200VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 937 | 200VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 938 | 200VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 939 | 200VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 300W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 942 | 220VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 943 | 220VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 944 | 220VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 945 | 220VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 946 | 220VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 947 | 220VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 948 | 220VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 949 | 220VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 950 | 220VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 951 | 220VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 952 | 220VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 953 | 220VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 954 | 220VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 955 | 220VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |

# 300W 250VDC-300VDC

| 300W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 958 | 250VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 959 | 250VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 960 | 250VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 961 | 250VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 962 | 250VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 963 | 250VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 964 | 250VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 965 | 250VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 966 | 250VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 967 | 250VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 968 | 250VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 969 | 250VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 970 | 250VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 971 | 250VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 300W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 974 | 280VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 975 | 280VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 976 | 280VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 977 | 280VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 978 | 280VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 979 | 280VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 980 | 280VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 981 | 280VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 982 | 280VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 983 | 280VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 984 | 280VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 985 | 280VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 986 | 280VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 987 | 280VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 300W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 990 | 300VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 991 | 300VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 992 | 300VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 993 | 300VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 994 | 300VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 995 | 300VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 996 | 300VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 997 | 300VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 998 | 300VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 999 | 300VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1000 | 300VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1001 | 300VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1002 | 300VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1003 | 300VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |

# 300W 350VDC-400VDC / 350W 12VDC

| 300W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1006 | 350VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1007 | 350VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1008 | 350VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1009 | 350VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1010 | 350VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1011 | 350VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1012 | 350VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1013 | 350VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1014 | 350VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1015 | 350VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1016 | 350VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1017 | 350VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1018 | 350VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1019 | 350VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 300W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1022 | 400VDC±15% | 12VDC±1-2% | 25A | 20A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1023 | 400VDC±15% | 24VDC±1-2% | 12.5A | 10A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1024 | 400VDC±15% | 36VDC±1-2% | 8.3A | 6.66A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1025 | 400VDC±15% | 48VDC±1-2% | 6.25A | 5A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1026 | 400VDC±15% | 64VDC±1-2% | 4.68A | 3.75A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1027 | 400VDC±15% | 100VDC±1-2% | 3A | 2.4A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1028 | 400VDC±15% | 150VDC±1-2% | 2A | 1.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1029 | 400VDC±15% | 200VDC±1-2% | 0.15A | 1.2A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1030 | 400VDC±15% | 220VDC±1-2% | 1.36A | 1.09A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1031 | 400VDC±15% | 250VDC±1-2% | 1.2A | 0.96A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1032 | 400VDC±15% | 280VDC±1-2% | 1.07A | 0.85A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1033 | 400VDC±15% | 300VDC±1-2% | 1A | 0.8A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1034 | 400VDC±15% | 350VDC±1-2% | 0.85A | 0.68A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 1035 | 400VDC±15% | 400VDC±1-2% | 0.75A | 0.6A | 300W | 240W | 199*110*50MM | 0.8KG/1KG |
| 350W 12VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1038 | 12VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1039 | 12VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1040 | 12VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1041 | 12VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1042 | 12VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1043 | 12VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1044 | 12VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1045 | 12VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1046 | 12VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1047 | 12VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1048 | 12VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1049 | 12VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1050 | 12VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1051 | 12VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |

| 350W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1054 | 24VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1055 | 24VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1056 | 24VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1057 | 24VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1058 | 24VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1059 | 24VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1060 | 24VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1061 | 24VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1062 | 24VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1063 | 24VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1064 | 24VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1065 | 24VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1066 | 24VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1067 | 24VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 350W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1070 | 36VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1071 | 36VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1072 | 36VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1073 | 36VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1074 | 36VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1075 | 36VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1076 | 36VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1077 | 36VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1078 | 36VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1079 | 36VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1080 | 36VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1081 | 36VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1082 | 36VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1083 | 36VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 350W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1086 | 48VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1087 | 48VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1088 | 48VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1089 | 48VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1090 | 48VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1091 | 48VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1092 | 48VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1093 | 48VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1094 | 48VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1095 | 48VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1096 | 48VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1097 | 48VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1098 | 48VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1099 | 48VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |

# 350W 64VDC-150VDC

| 350W 64VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1102 | 64VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1103 | 64VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1104 | 64VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1105 | 64VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1106 | 64VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1107 | 64VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1108 | 64VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1109 | 64VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1110 | 64VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1111 | 64VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1112 | 64VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1113 | 64VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1114 | 64VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1115 | 64VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 350W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1118 | 100VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1119 | 100VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1120 | 100VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1121 | 100VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1122 | 100VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1123 | 100VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1124 | 100VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1125 | 100VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1126 | 100VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1127 | 100VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1128 | 100VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1129 | 100VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1130 | 100VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1131 | 100VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 350W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1134 | 150VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1135 | 150VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1136 | 150VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1137 | 150VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1138 | 150VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1139 | 150VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1140 | 150VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1141 | 150VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1142 | 150VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1143 | 150VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1144 | 150VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1145 | 150VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1146 | 150VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1147 | 150VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |

| 350W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1150 | 200VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1151 | 200VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1152 | 200VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1153 | 200VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1154 | 200VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1155 | 200VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1156 | 200VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1157 | 200VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1158 | 200VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1159 | 200VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1160 | 200VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1161 | 200VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1162 | 200VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1163 | 200VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 350W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1166 | 250VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1167 | 250VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1168 | 250VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1169 | 250VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1170 | 250VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1171 | 250VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1172 | 250VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1173 | 250VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1174 | 250VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1175 | 250VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1176 | 250VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1177 | 250VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1178 | 250VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1179 | 250VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 350W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1182 | 280VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1183 | 280VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1184 | 280VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1185 | 280VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1186 | 280VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1187 | 280VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1188 | 280VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1189 | 280VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1190 | 280VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1191 | 280VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1192 | 280VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1193 | 280VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1194 | 280VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1195 | 280VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |

# 350W 300VDC-400VDC

| 350W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1198 | 300VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1199 | 300VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1200 | 300VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1201 | 300VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1202 | 300VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1203 | 300VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1204 | 300VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1205 | 300VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1206 | 300VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1207 | 300VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1208 | 300VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1209 | 300VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1210 | 300VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1211 | 300VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 350W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1214 | 350VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1215 | 350VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1216 | 350VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1217 | 350VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1218 | 350VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1219 | 350VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1220 | 350VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1221 | 350VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1222 | 350VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1223 | 350VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1224 | 350VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1225 | 350VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1226 | 350VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1227 | 350VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 350W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1230 | 400VDC±15% | 12VDC±1-2% | 29.1A | 23.3A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1231 | 400VDC±15% | 24VDC±1-2% | 14.5A | 11.6A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1232 | 400VDC±15% | 36VDC±1-2% | 9.7A | 7.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1233 | 400VDC±15% | 48VDC±1-2% | 7.29A | 5.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1234 | 400VDC±15% | 64VDC±1-2% | 5.46A | 4.375A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1235 | 400VDC±15% | 100VDC±1-2% | 3.5A | 2.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1236 | 400VDC±15% | 150VDC±1-2% | 2.3A | 1.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1237 | 400VDC±15% | 200VDC±1-2% | 1.75A | 1.4A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1238 | 400VDC±15% | 220VDC±1-2% | 1.59A | 1.27A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1239 | 400VDC±15% | 250VDC±1-2% | 1.4A | 1.12A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1240 | 400VDC±15% | 280VDC±1-2% | 1.25A | 1A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1241 | 400VDC±15% | 300VDC±1-2% | 1.16A | 0.93A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1242 | 400VDC±15% | 350VDC±1-2% | 1A | 0.8A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |
| 1243 | 400VDC±15% | 400VDC±1-2% | 0.875A | 0.7A | 350W | 280W | 199*110*50MM | 0.8KG/1KG |

# 400W 12VDC-36VDC

| 400W 12VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1246 | 12VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1247 | 12VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1248 | 12VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1249 | 12VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1250 | 12VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1251 | 12VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1252 | 12VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1253 | 12VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1254 | 12VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1255 | 12VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1256 | 12VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1257 | 12VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1258 | 12VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1259 | 12VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 400W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1262 | 24VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1263 | 24VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1264 | 24VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1265 | 24VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1266 | 24VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1267 | 24VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1268 | 24VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1269 | 24VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1270 | 24VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1271 | 24VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1272 | 24VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1273 | 24VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1274 | 24VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1275 | 24VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 400W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1278 | 36VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1279 | 36VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1280 | 36VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1281 | 36VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1282 | 36VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1283 | 36VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1284 | 36VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1285 | 36VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1286 | 36VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1287 | 36VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1288 | 36VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1289 | 36VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1290 | 36VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1291 | 36VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |

# 400W 48VDC-100VDC

| 400W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1294 | 48VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1295 | 48VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1296 | 48VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1297 | 48VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1298 | 48VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1299 | 48VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1300 | 48VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1301 | 48VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1302 | 48VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1303 | 48VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1304 | 48VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1305 | 48VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1306 | 48VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1307 | 48VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 400W 64VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1310 | 64VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1311 | 64VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1312 | 64VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1313 | 64VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1314 | 64VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1315 | 64VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1316 | 64VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1317 | 64VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1318 | 64VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1319 | 64VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1320 | 64VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1321 | 64VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1322 | 64VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1323 | 64VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 400W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1326 | 100VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1327 | 100VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1328 | 100VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1329 | 100VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1330 | 100VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1331 | 100VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1332 | 100VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1333 | 100VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1334 | 100VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1335 | 100VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1336 | 100VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1337 | 100VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1338 | 100VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1339 | 100VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |

| 400W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1342 | 150VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1343 | 150VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1344 | 150VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1345 | 150VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1346 | 150VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1347 | 150VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1348 | 150VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1349 | 150VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1350 | 150VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1351 | 150VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1352 | 150VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1353 | 150VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1354 | 150VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1355 | 150VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 400W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1358 | 200VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1359 | 200VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1360 | 200VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1361 | 200VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1362 | 200VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1363 | 200VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1364 | 200VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1365 | 200VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1366 | 200VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1367 | 200VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1368 | 200VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1369 | 200VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1370 | 200VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1371 | 200VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 400W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1374 | 220VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1375 | 220VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1376 | 220VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1377 | 220VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1378 | 220VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1379 | 220VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1380 | 220VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1381 | 220VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1382 | 220VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1383 | 220VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1384 | 220VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1385 | 220VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1386 | 220VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1387 | 220VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |

| 400W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1390 | 250VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1391 | 250VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1392 | 250VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1393 | 250VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1394 | 250VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1395 | 250VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1396 | 250VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1397 | 250VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1398 | 250VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1399 | 250VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1400 | 250VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1401 | 250VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1402 | 250VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1403 | 250VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 400W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1406 | 280VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1407 | 280VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1408 | 280VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1409 | 280VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1410 | 280VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1411 | 280VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1412 | 280VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1413 | 280VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1414 | 280VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1415 | 280VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1416 | 280VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1417 | 280VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1418 | 280VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1419 | 280VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 400W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1422 | 300VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1423 | 300VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1424 | 300VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1425 | 300VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1426 | 300VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1427 | 300VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1428 | 300VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1429 | 300VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1430 | 300VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1431 | 300VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1432 | 300VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1433 | 300VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1434 | 300VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1435 | 300VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |

# 400W 350VDC-400VDC / 500W 12VDC

| 400W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1438 | 350VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1439 | 350VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1440 | 350VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1441 | 350VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1442 | 350VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1443 | 350VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1444 | 350VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1445 | 350VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1446 | 350VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1447 | 350VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1448 | 350VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1449 | 350VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1450 | 350VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1451 | 350VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 400W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1454 | 400VDC±15% | 12VDC±1-2% | 33.3A | 26.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1455 | 400VDC±15% | 24VDC±1-2% | 16.6A | 13.3A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1456 | 400VDC±15% | 36VDC±1-2% | 11.1A | 8.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1457 | 400VDC±15% | 48VDC±1-2% | 8.3A | 6.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1458 | 400VDC±15% | 64VDC±1-2% | 6.25A | 5A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1459 | 400VDC±15% | 100VDC±1-2% | 4A | 3.2A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1460 | 400VDC±15% | 150VDC±1-2% | 2.6A | 2.1A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1461 | 400VDC±15% | 200VDC±1-2% | 2A | 1.6A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1462 | 400VDC±15% | 220VDC±1-2% | 1.8A | 1.45A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1463 | 400VDC±15% | 250VDC±1-2% | 1.6A | 1.28A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1464 | 400VDC±15% | 280VDC±1-2% | 1.4A | 1.14A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1465 | 400VDC±15% | 300VDC±1-2% | 1.3A | 1.06A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1466 | 400VDC±15% | 350VDC±1-2% | 1.14A | 0.91A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 1467 | 400VDC±15% | 400VDC±1-2% | 1A | 0.8A | 400W | 320W | 199*110*50MM | 0.8KG/1KG |
| 500W 12VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1470 | 12VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1471 | 12VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1472 | 12VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1473 | 12VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1474 | 12VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1475 | 12VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1476 | 12VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1477 | 12VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1478 | 12VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1479 | 12VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1480 | 12VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1481 | 12VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1482 | 12VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1483 | 12VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1484 | 12VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1485 | 12VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1486 | 12VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1487 | 12VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |

# 500W 24VDC-48VDC

| 500W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1490 | 24VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1491 | 24VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1492 | 24VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1493 | 24VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1494 | 24VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1495 | 24VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1496 | 24VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1497 | 24VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1498 | 24VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1499 | 24VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1500 | 24VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1501 | 24VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1502 | 24VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1503 | 24VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1504 | 24VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1505 | 24VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1506 | 24VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1507 | 24VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1510 | 36VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1511 | 36VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1512 | 36VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1513 | 36VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1514 | 36VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1515 | 36VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1516 | 36VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1517 | 36VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1518 | 36VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1519 | 36VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1520 | 36VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1521 | 36VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1522 | 36VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1523 | 36VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1524 | 36VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1525 | 36VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1526 | 36VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1527 | 36VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1530 | 48VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1531 | 48VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1532 | 48VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1533 | 48VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1534 | 48VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1535 | 48VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1536 | 48VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1537 | 48VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1538 | 48VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1539 | 48VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1540 | 48VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1541 | 48VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1542 | 48VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1543 | 48VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1544 | 48VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1545 | 48VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1546 | 48VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1547 | 48VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |

# 500W 60VDC-80VDC

| 500W 60VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1550 | 60VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1551 | 60VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1552 | 60VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1553 | 60VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1554 | 60VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1555 | 60VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1556 | 60VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1557 | 60VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1558 | 60VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1559 | 60VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1560 | 60VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1561 | 60VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1562 | 60VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1563 | 60VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1564 | 60VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1565 | 60VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1566 | 60VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1567 | 60VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 72VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1570 | 72VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1571 | 72VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1572 | 72VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1573 | 72VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1574 | 72VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1575 | 72VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1576 | 72VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1577 | 72VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1578 | 72VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1579 | 72VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1580 | 72VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1581 | 72VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1582 | 72VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1583 | 72VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1584 | 72VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1585 | 72VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1586 | 72VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1587 | 72VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 80VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1590 | 80VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1591 | 80VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1592 | 80VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1593 | 80VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1594 | 80VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1595 | 80VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1596 | 80VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1597 | 80VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1598 | 80VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1599 | 80VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1600 | 80VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1601 | 80VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1602 | 80VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1603 | 80VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1604 | 80VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1605 | 80VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1606 | 80VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1607 | 80VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |

# 500W 100VDC-150VDC

| 500W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1610 | 100VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1611 | 100VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1612 | 100VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1613 | 100VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1614 | 100VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1615 | 100VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1616 | 100VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1617 | 100VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1618 | 100VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1619 | 100VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1620 | 100VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1621 | 100VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1622 | 100VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1623 | 100VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1624 | 100VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1625 | 100VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1626 | 100VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1627 | 100VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 110VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1630 | 110VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1631 | 110VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1632 | 110VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1633 | 110VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1634 | 110VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1635 | 110VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1636 | 110VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1637 | 110VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1638 | 110VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1639 | 110VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1640 | 110VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1641 | 110VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1642 | 110VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1643 | 110VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1644 | 110VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1645 | 110VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1646 | 110VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1647 | 110VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1650 | 150VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1651 | 150VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1652 | 150VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1653 | 150VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1654 | 150VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1655 | 150VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1656 | 150VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1657 | 150VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1658 | 150VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1659 | 150VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1660 | 150VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1661 | 150VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1662 | 150VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1663 | 150VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1664 | 150VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1665 | 150VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1666 | 150VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1667 | 150VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |

# 500W 200VDC-250VDC

| 500W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1670 | 200VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1671 | 200VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1672 | 200VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1673 | 200VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1674 | 200VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1675 | 200VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1676 | 200VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1677 | 200VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1678 | 200VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1679 | 200VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1680 | 200VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1681 | 200VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1682 | 200VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1683 | 200VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1684 | 200VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1685 | 200VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1686 | 200VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1687 | 200VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1690 | 220VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1691 | 220VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1692 | 220VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1693 | 220VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1694 | 220VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1695 | 220VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1696 | 220VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1697 | 220VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1698 | 220VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1699 | 220VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1700 | 220VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1701 | 220VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1702 | 220VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1703 | 220VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1704 | 220VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1705 | 220VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1706 | 220VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1707 | 220VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1712 | 250VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1713 | 250VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1714 | 250VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1715 | 250VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1716 | 250VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1717 | 250VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1718 | 250VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1719 | 250VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1720 | 250VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1721 | 250VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1722 | 250VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1723 | 250VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1724 | 250VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1725 | 250VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1726 | 250VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1727 | 250VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1728 | 250VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1729 | 250VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |

# 500W 280VDC-350VDC

| 500W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1732 | 280VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1733 | 280VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1734 | 280VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1735 | 280VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1736 | 280VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1737 | 280VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1738 | 280VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1739 | 280VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1740 | 280VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1741 | 280VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1742 | 280VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1743 | 280VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1744 | 280VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1745 | 280VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1746 | 280VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1747 | 280VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1748 | 280VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1749 | 280VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1752 | 300VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1753 | 300VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1754 | 300VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1755 | 300VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1756 | 300VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1757 | 300VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1758 | 300VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1759 | 300VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1760 | 300VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1761 | 300VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1762 | 300VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1763 | 300VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1764 | 300VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1765 | 300VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1766 | 300VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1767 | 300VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1768 | 300VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1769 | 300VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1772 | 350VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1773 | 350VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1774 | 350VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1775 | 350VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1776 | 350VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1777 | 350VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1778 | 350VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1779 | 350VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1780 | 350VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1781 | 350VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1782 | 350VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1783 | 350VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1784 | 350VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1785 | 350VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1786 | 350VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1787 | 350VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1788 | 350VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1789 | 350VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |

# 500W 400VDC-500VDC

| 500W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1792 | 400VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1793 | 400VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1794 | 400VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1795 | 400VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1796 | 400VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1797 | 400VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1798 | 400VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1799 | 400VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1800 | 400VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1801 | 400VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1802 | 400VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1803 | 400VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1804 | 400VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1805 | 400VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1806 | 400VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1807 | 400VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1808 | 400VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1809 | 400VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 450VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1812 | 450VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1813 | 450VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1814 | 450VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1815 | 450VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1816 | 450VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1817 | 450VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1818 | 450VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1819 | 450VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1820 | 450VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1821 | 450VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1822 | 450VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1823 | 450VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1824 | 450VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1825 | 450VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1826 | 450VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1827 | 450VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1828 | 450VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1829 | 450VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 500VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1832 | 500VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1833 | 500VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1834 | 500VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1835 | 500VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1836 | 500VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1837 | 500VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1838 | 500VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1839 | 500VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1840 | 500VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1841 | 500VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1842 | 500VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1843 | 500VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1844 | 500VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1845 | 500VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1846 | 500VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1847 | 500VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1848 | 500VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1849 | 500VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |

# 500W 550VDC-600VDC / 600W 12VDC

| 500W 550VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1852 | 550VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1853 | 550VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1854 | 550VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1855 | 550VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1856 | 550VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1857 | 550VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1858 | 550VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1859 | 550VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1860 | 550VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1861 | 550VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1862 | 550VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1863 | 550VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1864 | 550VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1865 | 550VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1866 | 550VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1867 | 550VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1868 | 550VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1869 | 550VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 500W 600VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage | Output voltage | Max output current | Continuous current | Max power | Continuous power | Size (MM) L*H*W | NW/GW (G) |
| 1872 | 600VDC±15% | 12VDC±1-2% | 41A | 33A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1873 | 600VDC±15% | 24VDC±1-2% | 20.8A | 16.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1874 | 600VDC±15% | 36VDC±1-2% | 13.8A | 11.1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1875 | 600VDC±15% | 48VDC±1-2% | 10.4A | 8.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1876 | 600VDC±15% | 64VDC±1-2% | 7.8A | 6.25A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1877 | 600VDC±15% | 100VDC±1-2% | 5A | 4A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1878 | 600VDC±15% | 150VDC±1-2% | 3.3A | 2.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1879 | 600VDC±15% | 200VDC±1-2% | 2.5A | 2A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1880 | 600VDC±15% | 220VDC±1-2% | 2.27A | 1.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1881 | 600VDC±15% | 250VDC±1-2% | 2A | 1.6A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1882 | 600VDC±15% | 280VDC±1-2% | 1.78A | 1.42A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1883 | 600VDC±15% | 300VDC±1-2% | 1.6A | 1.3A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1884 | 600VDC±15% | 350VDC±1-2% | 1.42A | 1.14A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1885 | 600VDC±15% | 400VDC±1-2% | 1.25A | 1A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1886 | 600VDC±15% | 450VDC±1-2% | 1.1A | 0.89A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1887 | 600VDC±15% | 500VDC±1-2% | 1.0A | 0.8A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1888 | 600VDC±15% | 550VDC±1-2% | 0.9A | 0.73A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 1889 | 600VDC±15% | 600VDC±1-2% | 0.83A | 0.67A | 500W | 400W | 238*124*65MM | 1.25/1.5KG |
| 600W 12VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 1892 | 12VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1893 | 12VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1894 | 12VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1895 | 12VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1896 | 12VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1897 | 12VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1898 | 12VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1899 | 12VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1900 | 12VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1901 | 12VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1902 | 12VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1903 | 12VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1904 | 12VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1905 | 12VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1906 | 12VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1907 | 12VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1908 | 12VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1909 | 12VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1910 | 12VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

# 600W 24VDC-48VDC

## 600W 24VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 1913 | 24VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1914 | 24VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1915 | 24VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1916 | 24VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1917 | 24VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1918 | 24VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1919 | 24VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1920 | 24VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1921 | 24VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1922 | 24VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1923 | 24VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1924 | 24VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1925 | 24VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1926 | 24VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1927 | 24VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1928 | 24VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1929 | 24VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1930 | 24VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1931 | 24VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

## 600W 36VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 1934 | 36VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1935 | 36VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1936 | 36VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1937 | 36VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1938 | 36VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1939 | 36VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1940 | 36VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1941 | 36VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1942 | 36VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1943 | 36VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1944 | 36VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1945 | 36VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1946 | 36VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1947 | 36VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1948 | 36VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1949 | 36VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1950 | 36VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1951 | 36VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1952 | 36VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

## 600W 48VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 1955 | 48VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1956 | 48VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1957 | 48VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1958 | 48VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1959 | 48VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1960 | 48VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1961 | 48VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1962 | 48VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1963 | 48VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1964 | 48VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1965 | 48VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1966 | 48VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1967 | 48VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1968 | 48VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1969 | 48VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1970 | 48VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1971 | 48VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1972 | 48VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1973 | 48VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

# 600W 64VDC-150VDC

## 600W 64VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 1976 | 64VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1977 | 64VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1978 | 64VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1979 | 64VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1980 | 64VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1981 | 64VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1982 | 64VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1983 | 64VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1984 | 64VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1985 | 64VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1986 | 64VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1987 | 64VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1988 | 64VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1989 | 64VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1990 | 64VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1991 | 64VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1992 | 64VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1993 | 64VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 1994 | 64VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

## 600W 100VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 1997 | 100VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1998 | 100VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 1999 | 100VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2000 | 100VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2001 | 100VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2002 | 100VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2003 | 100VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2004 | 100VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2005 | 100VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2006 | 100VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2007 | 100VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2008 | 100VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2009 | 100VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2010 | 100VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2011 | 100VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2012 | 100VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2013 | 100VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2014 | 100VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2015 | 100VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

## 600W 150VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 2018 | 150VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2019 | 150VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2020 | 150VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2021 | 150VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2022 | 150VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2023 | 150VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2024 | 150VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2025 | 150VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2026 | 150VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2027 | 150VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2028 | 150VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2029 | 150VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2030 | 150VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2031 | 150VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2032 | 150VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2033 | 150VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2034 | 150VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2035 | 150VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2036 | 150VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

# 600W 200VDC-250VDC

## 600W 200VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 2039 | 200VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2040 | 200VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2041 | 200VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2042 | 200VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2043 | 200VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2044 | 200VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2045 | 200VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2046 | 200VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2047 | 200VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2048 | 200VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2049 | 200VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2050 | 200VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2051 | 200VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2052 | 200VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2053 | 200VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2054 | 200VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2055 | 200VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2056 | 200VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2057 | 200VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

## 600W 220VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 2060 | 220VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2061 | 220VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2062 | 220VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2063 | 220VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2064 | 220VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2065 | 220VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2066 | 220VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2067 | 220VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2068 | 220VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2069 | 220VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2070 | 220VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2071 | 220VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2072 | 220VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2073 | 220VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2074 | 220VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2075 | 220VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2076 | 220VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2077 | 220VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2078 | 220VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

## 600W 250VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 2081 | 250VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2082 | 250VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2083 | 250VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2084 | 250VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2085 | 250VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2086 | 250VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2087 | 250VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2088 | 250VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2089 | 250VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2090 | 250VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2091 | 250VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2092 | 250VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2093 | 250VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2094 | 250VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2095 | 250VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2096 | 250VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2097 | 250VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2098 | 250VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2099 | 250VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

# 600W 280VDC-310VDC

| 600W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2102 | 280VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2103 | 280VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2104 | 280VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2105 | 280VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2106 | 280VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2107 | 280VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2108 | 280VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2109 | 280VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2110 | 280VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2111 | 280VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2112 | 280VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2113 | 280VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2114 | 280VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2115 | 280VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2116 | 280VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2117 | 280VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2118 | 280VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2119 | 280VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2120 | 280VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 600W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2123 | 300VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2124 | 300VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2125 | 300VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2126 | 300VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2127 | 300VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2128 | 300VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2129 | 300VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2130 | 300VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2131 | 300VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2132 | 300VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2133 | 300VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2134 | 300VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2135 | 300VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2136 | 300VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2137 | 300VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2138 | 300VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2139 | 300VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2140 | 300VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2141 | 300VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 600W 310VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2144 | 310VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2145 | 310VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2146 | 310VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2147 | 310VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2148 | 310VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2149 | 310VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2150 | 310VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2151 | 310VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2152 | 310VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2153 | 310VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2154 | 310VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2155 | 310VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2156 | 310VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2157 | 310VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2158 | 310VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2159 | 310VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2160 | 310VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2161 | 310VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2162 | 310VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

# 600W 350VDC-450VDC

## 600W 350VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 2165 | 350VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2166 | 350VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2167 | 350VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2168 | 350VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2169 | 350VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2170 | 350VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2171 | 350VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2172 | 350VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2173 | 350VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2174 | 350VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2175 | 350VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2176 | 350VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2177 | 350VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2178 | 350VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2179 | 350VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2180 | 350VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2181 | 350VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2182 | 350VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2183 | 350VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

## 600W 400VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 2186 | 400VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2187 | 400VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2188 | 400VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2189 | 400VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2190 | 400VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2191 | 400VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2192 | 400VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2193 | 400VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2194 | 400VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2195 | 400VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2196 | 400VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2197 | 400VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2198 | 400VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2199 | 400VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2200 | 400VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2201 | 400VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2202 | 400VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2203 | 400VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2204 | 400VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

## 600W 450VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 2207 | 450VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2208 | 450VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2209 | 450VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2210 | 450VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2211 | 450VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2212 | 450VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2213 | 450VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2214 | 450VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2215 | 450VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2216 | 450VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2217 | 450VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2218 | 450VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2219 | 450VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2220 | 450VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2221 | 450VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2222 | 450VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2223 | 450VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2224 | 450VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2225 | 450VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

# 600W 500VDC-600VDC

## 600W 500VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 2228 | 500VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2229 | 500VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2230 | 500VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2231 | 500VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2232 | 500VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2233 | 500VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2234 | 500VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2235 | 500VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2236 | 500VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2237 | 500VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2238 | 500VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2239 | 500VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2240 | 500VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2241 | 500VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2242 | 500VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2243 | 500VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2244 | 500VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2245 | 500VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2246 | 500VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

## 600W 550VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 2249 | 550VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2250 | 550VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2251 | 550VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2252 | 550VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2253 | 550VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2254 | 550VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2255 | 550VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2256 | 550VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2257 | 550VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2258 | 550VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2259 | 550VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2260 | 550VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2261 | 550VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2262 | 550VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2263 | 550VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2264 | 550VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2265 | 550VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2266 | 550VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2267 | 550VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

## 600W 600VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 2270 | 600VDC±15% | 12VDC±1-2% | 50A | 40A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2271 | 600VDC±15% | 24VDC±1-2% | 25A | 20A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2272 | 600VDC±15% | 36VDC±1-2% | 16.6A | 13.3A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2273 | 600VDC±15% | 48VDC±1-2% | 12.5A | 10A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2274 | 600VDC±15% | 64VDC±1-2% | 9.37A | 7.5A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2275 | 600VDC±15% | 100VDC±1-2% | 6A | 4.8A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2276 | 600VDC±15% | 150VDC±1-2% | 4A | 3.2A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2277 | 600VDC±15% | 200VDC±1-2% | 3A | 2.4A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2278 | 600VDC±15% | 220VDC±1-2% | 2.7A | 2.18A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2279 | 600VDC±15% | 250VDC±1-2% | 2.4A | 1.92A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2280 | 600VDC±15% | 280VDC±1-2% | 2.14A | 1.71A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2281 | 600VDC±15% | 300VDC±1-2% | 2A | 1.6A | 600W | 480W | 238*124*65MM | 1.25/1.5KG |
| 2282 | 600VDC±15% | 310VDC±1-2% | 1.9A | 1.5A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2283 | 600VDC±15% | 350VDC±1-2% | 1.7A | 1.37A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2284 | 600VDC±15% | 400VDC±1-2% | 1.5A | 1.2A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2285 | 600VDC±15% | 450VDC±1-2% | 1.3A | 1A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2286 | 600VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2287 | 600VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2288 | 600VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2289 | 600VDC±15% | 650VDC±1-2% | 0.92A | 0.74A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2290 | 600VDC±15% | 700VDC±1-2% | 0.86A | 0.69A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2291 | 650VDC±15% | 500VDC±1-2% | 1.2A | 0.96A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2292 | 650VDC±15% | 550VDC±1-2% | 1.09A | 0.87A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2293 | 650VDC±15% | 600VDC±1-2% | 1A | 0.8A | 600W | 600W | 238*124*65MM | 1.25/1.5KG |

# 750W 12VDC-36VDC

| 750W 12VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2296 | 12VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2297 | 12VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2298 | 12VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2299 | 12VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2300 | 12VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2301 | 12VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2302 | 12VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2303 | 12VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2304 | 12VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2305 | 12VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2306 | 12VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2307 | 12VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2308 | 12VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2309 | 12VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2310 | 12VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2311 | 12VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2312 | 12VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2313 | 12VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2314 | 12VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2315 | 12VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2316 | 12VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2319 | 24VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2320 | 24VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2321 | 24VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2322 | 24VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2323 | 24VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2324 | 24VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2325 | 24VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2326 | 24VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2327 | 24VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2328 | 24VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2329 | 24VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2330 | 24VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2331 | 24VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2332 | 24VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2333 | 24VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2334 | 24VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2335 | 24VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2336 | 24VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2337 | 24VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2338 | 24VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2339 | 24VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2342 | 36VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2343 | 36VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2344 | 36VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2345 | 36VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2346 | 36VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2347 | 36VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2348 | 36VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2349 | 36VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2350 | 36VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2351 | 36VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2352 | 36VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2353 | 36VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2354 | 36VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2355 | 36VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2356 | 36VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2357 | 36VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2358 | 36VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2359 | 36VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2360 | 36VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2361 | 36VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2362 | 36VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |

# 750W 48VDC-80VDC

| 750W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2365 | 48VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2366 | 48VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2367 | 48VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2368 | 48VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2369 | 48VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2370 | 48VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2371 | 48VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2372 | 48VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2373 | 48VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2374 | 48VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2375 | 48VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2376 | 48VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2377 | 48VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2378 | 48VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2379 | 48VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2380 | 48VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2381 | 48VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2382 | 48VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2383 | 48VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2384 | 48VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2385 | 48VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 64VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2388 | 64VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2389 | 64VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2390 | 64VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2391 | 64VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2392 | 64VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2393 | 64VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2394 | 64VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2395 | 64VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2396 | 64VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2397 | 64VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2398 | 64VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2399 | 64VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2400 | 64VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2401 | 64VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2402 | 64VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2403 | 64VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2404 | 64VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2405 | 64VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2406 | 64VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2407 | 64VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2408 | 64VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 80VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2411 | 80VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2412 | 80VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2413 | 80VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2414 | 80VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2415 | 80VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2416 | 80VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2417 | 80VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2418 | 80VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2419 | 80VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2420 | 80VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2421 | 80VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2422 | 80VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2423 | 80VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2424 | 80VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2425 | 80VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2426 | 80VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2427 | 80VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2428 | 80VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2429 | 80VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2430 | 80VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2431 | 80VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |

# 750W 100VDC-150VDC

| 750W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2434 | 100VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2435 | 100VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2436 | 100VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2437 | 100VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2438 | 100VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2439 | 100VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2440 | 100VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2441 | 100VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2442 | 100VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2443 | 100VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2444 | 100VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2445 | 100VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2446 | 100VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2447 | 100VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2448 | 100VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2449 | 100VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2450 | 100VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2451 | 100VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2452 | 100VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2453 | 100VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2454 | 100VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 110VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2457 | 110VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2458 | 110VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2459 | 110VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2460 | 110VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2461 | 110VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2462 | 110VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2463 | 110VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2464 | 110VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2465 | 110VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2466 | 110VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2467 | 110VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2468 | 110VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2469 | 110VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2470 | 110VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2471 | 110VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2472 | 110VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2473 | 110VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2474 | 110VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2475 | 110VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2476 | 110VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2477 | 110VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2480 | 150VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2481 | 150VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2482 | 150VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2483 | 150VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2484 | 150VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2485 | 150VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2486 | 150VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2487 | 150VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2488 | 150VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2489 | 150VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2490 | 150VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2491 | 150VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2492 | 150VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2493 | 150VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2494 | 150VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2495 | 150VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2496 | 150VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2497 | 150VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2498 | 150VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2499 | 150VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2500 | 150VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |

# 750W 200VDC-250VDC

| 750W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2503 | 200VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2504 | 200VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2505 | 200VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2506 | 200VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2507 | 200VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2508 | 200VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2509 | 200VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2510 | 200VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2511 | 200VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2512 | 200VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2513 | 200VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2514 | 200VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2515 | 200VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2516 | 200VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2517 | 200VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2518 | 200VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2519 | 200VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2520 | 200VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2521 | 200VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2522 | 200VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2523 | 200VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2526 | 220VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2527 | 220VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2528 | 220VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2529 | 220VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2530 | 220VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2531 | 220VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2532 | 220VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2533 | 220VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2534 | 220VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2535 | 220VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2536 | 220VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2537 | 220VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2538 | 220VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2539 | 220VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2540 | 220VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2541 | 220VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2542 | 220VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2543 | 220VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2544 | 220VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2545 | 220VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2546 | 220VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2549 | 250VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2550 | 250VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2551 | 250VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2552 | 250VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2553 | 250VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2554 | 250VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2555 | 250VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2556 | 250VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2557 | 250VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2558 | 250VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2559 | 250VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2560 | 250VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2561 | 250VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2562 | 250VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2563 | 250VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2564 | 250VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2565 | 250VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2566 | 250VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2567 | 250VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2568 | 250VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2569 | 250VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |

# 750W 280VDC-310VDC

| 750W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2572 | 280VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2573 | 280VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2574 | 280VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2575 | 280VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2576 | 280VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2577 | 280VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2578 | 280VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2579 | 280VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2580 | 280VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2581 | 280VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2582 | 280VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2583 | 280VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2584 | 280VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2585 | 280VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2586 | 280VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2587 | 280VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2588 | 280VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2589 | 280VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2590 | 280VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2591 | 280VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2592 | 280VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2595 | 300VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2596 | 300VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2597 | 300VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2598 | 300VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2599 | 300VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2600 | 300VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2601 | 300VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2602 | 300VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2603 | 300VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2604 | 300VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2605 | 300VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2606 | 300VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2607 | 300VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2608 | 300VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2609 | 300VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2610 | 300VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2611 | 300VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2612 | 300VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2613 | 300VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2614 | 300VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2615 | 300VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 310VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2618 | 310VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2619 | 310VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2620 | 310VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2621 | 310VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2622 | 310VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2623 | 310VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2624 | 310VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2625 | 310VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2626 | 310VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2627 | 310VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2628 | 310VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2629 | 310VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2630 | 310VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2631 | 310VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2632 | 310VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2633 | 310VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2634 | 310VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2635 | 310VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2636 | 310VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2637 | 310VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2638 | 310VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |

# 750W 360VDC-480VDC

| 750W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L+H+W | NW/GW (G) |
| 2641 | 350VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2642 | 350VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2643 | 350VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2644 | 350VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2645 | 350VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2646 | 350VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2647 | 350VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2648 | 350VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2649 | 350VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2650 | 350VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2651 | 350VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2652 | 350VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2653 | 350VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2654 | 350VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2655 | 350VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2656 | 350VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2657 | 350VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2658 | 350VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2659 | 350VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2660 | 350VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2661 | 350VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L+H+W | NW/GW (G) |
| 2664 | 400VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2665 | 400VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2666 | 400VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2667 | 400VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2668 | 400VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2669 | 400VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2670 | 400VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2671 | 400VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2672 | 400VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2673 | 400VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2674 | 400VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2675 | 400VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2676 | 400VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2677 | 400VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2678 | 400VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2679 | 400VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2680 | 400VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2681 | 400VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2682 | 400VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2683 | 400VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2684 | 400VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 450VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L+H+W | NW/GW (G) |
| 2687 | 450VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2688 | 450VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2689 | 450VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2690 | 450VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2691 | 450VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2692 | 450VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2693 | 450VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2694 | 450VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2695 | 450VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2696 | 450VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2697 | 450VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2698 | 450VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2699 | 450VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2700 | 450VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2701 | 450VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2702 | 450VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2703 | 450VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2704 | 450VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2705 | 450VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2706 | 450VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2707 | 450VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |

# 750W 500VDC-600VDC

| 750W 500VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L+H+W | NW/GW (G) |
| 2710 | 500VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2711 | 500VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2712 | 500VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2713 | 500VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2714 | 500VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2715 | 500VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2716 | 500VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2717 | 500VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2718 | 500VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2719 | 500VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2720 | 500VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2721 | 500VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2722 | 500VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2723 | 500VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2724 | 500VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2725 | 500VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2726 | 500VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2727 | 500VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2728 | 500VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2729 | 500VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2730 | 500VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 550VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L+H+W | NW/GW (G) |
| 2733 | 550VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2734 | 550VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2735 | 550VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2736 | 550VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2737 | 550VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2738 | 550VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2739 | 550VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2740 | 550VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2741 | 550VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2742 | 550VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2743 | 550VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2744 | 550VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2745 | 550VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2746 | 550VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2747 | 550VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2748 | 550VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2749 | 550VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2750 | 550VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2751 | 550VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2752 | 550VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2753 | 550VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 750W 600VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L+H+W | NW/GW (G) |
| 2756 | 600VDC±15% | 12VDC±1-2% | 62A | 50A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2757 | 600VDC±15% | 24VDC±1-2% | 31A | 25A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2758 | 600VDC±15% | 36VDC±1-2% | 20A | 16.6A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2759 | 600VDC±15% | 48VDC±1-2% | 15.6A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2760 | 600VDC±15% | 64VDC±1-2% | 11.7A | 12.5A | 750W | 600W | 238*124*65MM | 1.25/1.5KG |
| 2761 | 600VDC±15% | 80VDC±1-2% | 9.3A | 7.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2762 | 600VDC±15% | 100VDC±1-2% | 7.5A | 6A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2763 | 600VDC±15% | 110VDC±1-2% | 6.8A | 5.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2764 | 600VDC±15% | 150VDC±1-2% | 5A | 4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2765 | 600VDC±15% | 200VDC±1-2% | 3.75A | 3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2766 | 600VDC±15% | 220VDC±1-2% | 3.4A | 2.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2767 | 600VDC±15% | 250VDC±1-2% | 3A | 2.4A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2768 | 600VDC±15% | 280VDC±1-2% | 2.67A | 2.14A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2769 | 600VDC±15% | 300VDC±1-2% | 2.5A | 2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2770 | 600VDC±15% | 310VDC±1-2% | 2.4A | 1.9A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2771 | 600VDC±15% | 350VDC±1-2% | 2.1A | 1.7A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2772 | 600VDC±15% | 400VDC±1-2% | 1.8A | 1.5A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2773 | 600VDC±15% | 450VDC±1-2% | 1.6A | 1.3A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2774 | 600VDC±15% | 500VDC±1-2% | 1.5A | 1.2A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2775 | 600VDC±15% | 550VDC±1-2% | 1.3A | 1.1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |
| 2776 | 600VDC±15% | 600VDC±1-2% | 1.2A | 1A | 750W | 750W | 238*124*65MM | 1.25/1.5KG |

# 1000W 12VDC-26VDC

| 1000W 12VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2779 | 12VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2780 | 12VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2781 | 12VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2782 | 12VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2783 | 12VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2784 | 12VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2785 | 12VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2786 | 12VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2787 | 12VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2788 | 12VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2789 | 12VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2790 | 12VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2791 | 12VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2792 | 12VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2793 | 12VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2794 | 12VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2795 | 12VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2796 | 12VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2797 | 12VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2798 | 12VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2799 | 12VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2800 | 12VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| **1000W 24VDC INPUT ISOLATE DC DC CONVERTER** | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2803 | 24VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2804 | 24VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2805 | 24VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2806 | 24VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2807 | 24VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2808 | 24VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2809 | 24VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2810 | 24VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2811 | 24VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2812 | 24VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2813 | 24VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2814 | 24VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2815 | 24VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2816 | 24VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2817 | 24VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2818 | 24VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2819 | 24VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2820 | 24VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2821 | 24VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2822 | 24VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2823 | 24VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2824 | 24VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| **1000W 36VDC INPUT ISOLATE DC DC CONVERTER** | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2827 | 36VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2828 | 36VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2829 | 36VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2830 | 36VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2831 | 36VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2832 | 36VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2833 | 36VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2834 | 36VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2835 | 36VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2836 | 36VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2837 | 36VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2838 | 36VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2839 | 36VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2840 | 36VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2841 | 36VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2842 | 36VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2843 | 36VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2844 | 36VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2845 | 36VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2846 | 36VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2847 | 36VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2848 | 36VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |

# 1000W 48VDC-72VDC

| 1000W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2851 | 48VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2852 | 48VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2853 | 48VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2854 | 48VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2855 | 48VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2856 | 48VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2857 | 48VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2858 | 48VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2859 | 48VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2860 | 48VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2861 | 48VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2862 | 48VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2863 | 48VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2864 | 48VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2865 | 48VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2866 | 48VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2867 | 48VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2868 | 48VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2869 | 48VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2870 | 48VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2871 | 48VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2872 | 48VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 1000W 60VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2875 | 60VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2876 | 60VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2877 | 60VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2878 | 60VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2879 | 60VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2880 | 60VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2881 | 60VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2882 | 60VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2883 | 60VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2884 | 60VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2885 | 60VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2886 | 60VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2887 | 60VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2888 | 60VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2889 | 60VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2890 | 60VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2891 | 60VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2892 | 60VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2893 | 60VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2894 | 60VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2895 | 60VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2896 | 60VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 1000W 72VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2899 | 72VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2900 | 72VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2901 | 72VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2902 | 72VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2903 | 72VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2904 | 72VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2905 | 72VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2906 | 72VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2907 | 72VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2908 | 72VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2909 | 72VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2910 | 72VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2911 | 72VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2912 | 72VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2913 | 72VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2914 | 72VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2915 | 72VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2916 | 72VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2917 | 72VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2918 | 72VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2919 | 72VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2920 | 72VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |

# 1000W 80VDC-110VDC

| 1000W 80VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2923 | 80VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2924 | 80VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2925 | 80VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2926 | 80VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2927 | 80VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2928 | 80VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2929 | 80VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2930 | 80VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2931 | 80VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2932 | 80VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2933 | 80VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2934 | 80VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2935 | 80VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2936 | 80VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2937 | 80VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2938 | 80VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2939 | 80VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2940 | 80VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2941 | 80VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2942 | 80VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2943 | 80VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2944 | 80VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 1000W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2947 | 100VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2948 | 100VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2949 | 100VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2950 | 100VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2951 | 100VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2952 | 100VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2953 | 100VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2954 | 100VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2955 | 100VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2956 | 100VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2957 | 100VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2958 | 100VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2959 | 100VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2960 | 100VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2961 | 100VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2962 | 100VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2963 | 100VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2964 | 100VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2965 | 100VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2966 | 100VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2967 | 100VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2968 | 100VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 1000W 110VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2971 | 110VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2972 | 110VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2973 | 110VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2974 | 110VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2975 | 110VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2976 | 110VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2977 | 110VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2978 | 110VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2979 | 110VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2980 | 110VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2981 | 110VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2982 | 110VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2983 | 110VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2984 | 110VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2985 | 110VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2986 | 110VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2987 | 110VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2988 | 110VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2989 | 110VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2990 | 110VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2991 | 110VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2992 | 110VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |

# 1000W 150VDC-220VDC

| 1000W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 2995 | 150VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 2996 | 150VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2997 | 150VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2998 | 150VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 2999 | 150VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3000 | 150VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3001 | 150VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3002 | 150VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3003 | 150VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3004 | 150VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3005 | 150VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3006 | 150VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3007 | 150VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3008 | 150VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3009 | 150VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3010 | 150VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3011 | 150VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3012 | 150VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3013 | 150VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3014 | 150VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3015 | 150VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3016 | 150VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 1000W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3019 | 200VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 3020 | 200VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3021 | 200VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3022 | 200VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3023 | 200VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3024 | 200VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3025 | 200VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3026 | 200VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3027 | 200VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3028 | 200VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3029 | 200VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3030 | 200VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3031 | 200VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3032 | 200VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3033 | 200VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3034 | 200VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3035 | 200VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3036 | 200VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3037 | 200VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3038 | 200VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3039 | 200VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3040 | 200VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 1000W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3043 | 220VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 3044 | 220VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3045 | 220VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3046 | 220VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3047 | 220VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3048 | 220VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3049 | 220VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3050 | 220VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3051 | 220VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3052 | 220VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3053 | 220VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3054 | 220VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3055 | 220VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3056 | 220VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3057 | 220VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3058 | 220VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3059 | 220VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3060 | 220VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3061 | 220VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3062 | 220VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3063 | 220VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3064 | 220VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |

# 1000W 250VDC-300VDC

| 1000W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3067 | 250VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 3068 | 250VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3069 | 250VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3070 | 250VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3071 | 250VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3072 | 250VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3073 | 250VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3074 | 250VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3075 | 250VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3076 | 250VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3077 | 250VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3078 | 250VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3079 | 250VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3080 | 250VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3081 | 250VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3082 | 250VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3083 | 250VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3084 | 250VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3085 | 250VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3086 | 250VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3087 | 250VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3088 | 250VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 1000W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3091 | 280VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 3092 | 280VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3093 | 280VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3094 | 280VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3095 | 280VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3096 | 280VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3097 | 280VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3098 | 280VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3099 | 280VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3100 | 280VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3101 | 280VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3102 | 280VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3103 | 280VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3104 | 280VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3105 | 280VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3106 | 280VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3107 | 280VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3108 | 280VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3109 | 280VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3110 | 280VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3111 | 280VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3112 | 280VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 1000W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3115 | 300VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 3116 | 300VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3117 | 300VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3118 | 300VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3119 | 300VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3120 | 300VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3121 | 300VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3122 | 300VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3123 | 300VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3124 | 300VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3125 | 300VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3126 | 300VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3127 | 300VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3128 | 300VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3129 | 300VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3130 | 300VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3131 | 300VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3132 | 300VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3133 | 300VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3134 | 300VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3135 | 300VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3136 | 300VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |

# 1000W 350VDC-400VDC

| 1000W 310VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3139 | 310VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 3140 | 310VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3141 | 310VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3142 | 310VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3143 | 310VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3144 | 310VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3145 | 310VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3146 | 310VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3147 | 310VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3148 | 310VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3149 | 310VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3150 | 310VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3151 | 310VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3152 | 310VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3153 | 310VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3154 | 310VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3155 | 310VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3156 | 310VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3157 | 310VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3158 | 310VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3159 | 310VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3160 | 310VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 1000W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3163 | 350VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 3164 | 350VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3165 | 350VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3166 | 350VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3167 | 350VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3168 | 350VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3169 | 350VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3170 | 350VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3171 | 350VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3172 | 350VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3173 | 350VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3174 | 350VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3175 | 350VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3176 | 350VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3177 | 350VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3178 | 350VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3179 | 350VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3180 | 350VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3181 | 350VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3182 | 350VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3183 | 350VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3184 | 350VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 1000W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3187 | 400VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 3188 | 400VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3189 | 400VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3190 | 400VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3191 | 400VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3192 | 400VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3193 | 400VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3194 | 400VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3195 | 400VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3196 | 400VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3197 | 400VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3198 | 400VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3199 | 400VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3200 | 400VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3201 | 400VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3202 | 400VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3203 | 400VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3204 | 400VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3205 | 400VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3206 | 400VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3207 | 400VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3208 | 400VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |

# 1000W 450VDC-500VDC

| 1000W 450VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3211 | 450VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 3212 | 450VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3213 | 450VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3214 | 450VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3215 | 450VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3216 | 450VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3217 | 450VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3218 | 450VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3219 | 450VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3220 | 450VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3221 | 450VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3222 | 450VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3223 | 450VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3224 | 450VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3225 | 450VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3226 | 450VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3227 | 450VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3228 | 450VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3229 | 450VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3230 | 450VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3231 | 450VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3232 | 450VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 1000W 500VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3235 | 500VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 3236 | 500VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3237 | 500VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3238 | 500VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3239 | 500VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3240 | 500VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3241 | 500VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3242 | 500VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3243 | 500VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3244 | 500VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3245 | 500VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3246 | 500VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3247 | 500VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3248 | 500VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3249 | 500VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3250 | 500VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3251 | 500VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3252 | 500VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3253 | 500VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3254 | 500VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3255 | 500VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3256 | 500VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 1000W 550VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3259 | 550VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 3260 | 550VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3261 | 550VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3262 | 550VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3263 | 550VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3264 | 550VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3265 | 550VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3266 | 550VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3267 | 550VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3268 | 550VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3269 | 550VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3270 | 550VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3271 | 550VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3272 | 550VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3273 | 550VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3274 | 550VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3275 | 550VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3276 | 550VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3277 | 550VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3278 | 550VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3279 | 550VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3280 | 550VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |

# 1000W 600VDC / 1500W 12VDC-24VDC

## 1000W 600VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 3283 | 600VDC±15% | 12VDC±1-2% | 83.3A | 66.6A | 1000W | 500W | 238*124*65MM | 1.25/1.5KG |
| 3284 | 600VDC±15% | 24VDC±1-2% | 41.6A | 33.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3285 | 600VDC±15% | 36VDC±1-2% | 27.7A | 22.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3286 | 600VDC±15% | 48VDC±1-2% | 20.8A | 16.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3287 | 600VDC±15% | 60VDC±1-2% | 16.6A | 13.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3288 | 600VDC±15% | 72VDC±1-2% | 13.8A | 11A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3289 | 600VDC±15% | 80VDC±1-2% | 12.5A | 10A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3290 | 600VDC±15% | 100VDC±1-2% | 10A | 8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3291 | 600VDC±15% | 110VDC±1-2% | 6.6A | 7.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3292 | 600VDC±15% | 150VDC±1-2% | 6.6A | 5.3A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3293 | 600VDC±15% | 200VDC±1-2% | 5A | 4A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3294 | 600VDC±15% | 220VDC±1-2% | 4.5A | 3.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3295 | 600VDC±15% | 250VDC±1-2% | 4A | 3.2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3296 | 600VDC±15% | 280VDC±1-2% | 3.57A | 2.8A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3297 | 600VDC±15% | 300VDC±1-2% | 3.33A | 2.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3298 | 600VDC±15% | 310VDC±1-2% | 3.2A | 2.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3299 | 600VDC±15% | 350VDC±1-2% | 2.85A | 2.28A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3300 | 600VDC±15% | 400VDC±1-2% | 2.5A | 2A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3301 | 600VDC±15% | 450VDC±1-2% | 2.22A | 1.78A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3302 | 600VDC±15% | 500VDC±1-2% | 2.0A | 1.6A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3303 | 600VDC±15% | 550VDC±1-2% | 1.82A | 1.5A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |
| 3304 | 600VDC±15% | 600VDC±1-2% | 1.67A | 1.33A | 1000W | 800W | 238*124*65MM | 1.25/1.5KG |

## 1500W 12VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 3307 | 12VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3308 | 12VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3309 | 12VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3310 | 12VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3311 | 12VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3312 | 12VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3313 | 12VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3314 | 12VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3315 | 12VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3316 | 12VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3317 | 12VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3318 | 12VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3319 | 12VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3320 | 12VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3321 | 12VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3322 | 12VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3323 | 12VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3324 | 12VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 750W | 440*300*110MM | 5/7KG |

## 1500W 24VDC INPUT ISOLATE DC DC CONVERTER

| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
|---|---|---|---|---|---|---|---|---|
| 3327 | 24VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3328 | 24VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3329 | 24VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3330 | 24VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3331 | 24VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3332 | 24VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3333 | 24VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3334 | 24VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3335 | 24VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3336 | 24VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3337 | 24VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3338 | 24VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3339 | 24VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3340 | 24VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3341 | 24VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3342 | 24VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3343 | 24VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3344 | 24VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |

# 1500W 36VDC-60VDC

| 1500W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3347 | 36VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3348 | 36VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3349 | 36VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3350 | 36VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3351 | 36VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3352 | 36VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3353 | 36VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3354 | 36VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3355 | 36VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3356 | 36VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3357 | 36VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3358 | 36VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3359 | 36VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3360 | 36VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3361 | 36VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3362 | 36VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3363 | 36VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3364 | 36VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 1500W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3367 | 48VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3368 | 48VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3369 | 48VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3370 | 48VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3371 | 48VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3372 | 48VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3373 | 48VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3374 | 48VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3375 | 48VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3376 | 48VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3377 | 48VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3378 | 48VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3379 | 48VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3380 | 48VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3381 | 48VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3382 | 48VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3383 | 48VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3384 | 48VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 1500W 60VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3387 | 60VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3388 | 60VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3389 | 60VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3390 | 60VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3391 | 60VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3392 | 60VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3393 | 60VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3394 | 60VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3395 | 60VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3396 | 60VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3397 | 60VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3398 | 60VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3399 | 60VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3400 | 60VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3401 | 60VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3402 | 60VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3403 | 60VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3404 | 60VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |

# 1500W 72VDC-100VDC

| 1500W 72VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3407 | 72VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3408 | 72VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3409 | 72VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3410 | 72VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3411 | 72VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3412 | 72VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3413 | 72VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3414 | 72VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3415 | 72VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3416 | 72VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3417 | 72VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3418 | 72VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3419 | 72VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3420 | 72VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3421 | 72VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3422 | 72VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3423 | 72VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3424 | 72VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 1500W 80VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3427 | 80VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3428 | 80VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3429 | 80VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3430 | 80VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3431 | 80VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3432 | 80VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3433 | 80VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3434 | 80VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3435 | 80VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3436 | 80VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3437 | 80VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3438 | 80VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3439 | 80VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3440 | 80VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3441 | 80VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3442 | 80VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3443 | 80VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3444 | 80VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 1500W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3447 | 100VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3448 | 100VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3449 | 100VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3450 | 100VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3451 | 100VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3452 | 100VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3453 | 100VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3454 | 100VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3455 | 100VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3456 | 100VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3457 | 100VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3458 | 100VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3459 | 100VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3460 | 100VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3461 | 100VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3462 | 100VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3463 | 100VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3464 | 100VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |

# 1500W 110VDC-200VDC

| 1500W 110VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3467 | 110VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3468 | 110VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3469 | 110VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3470 | 110VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3471 | 110VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3472 | 110VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3473 | 110VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3474 | 110VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3475 | 110VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3476 | 110VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3477 | 110VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3478 | 110VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3479 | 110VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3480 | 110VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3481 | 110VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3482 | 110VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3483 | 110VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3484 | 110VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 1500W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3487 | 150VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3488 | 150VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3489 | 150VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3490 | 150VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3491 | 150VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3492 | 150VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3493 | 150VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3494 | 150VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3495 | 150VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3496 | 150VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3497 | 150VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3498 | 150VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3499 | 150VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3500 | 150VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3501 | 150VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3502 | 150VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3503 | 150VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3504 | 150VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 1500W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3507 | 200VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3508 | 200VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3509 | 200VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3510 | 200VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3511 | 200VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3512 | 200VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3513 | 200VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3514 | 200VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3515 | 200VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3516 | 200VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3517 | 200VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3518 | 200VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3519 | 200VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3520 | 200VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3521 | 200VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3522 | 200VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3523 | 200VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3524 | 200VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |

# 1500W 250VDC-300VDC

| 1500W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3527 | 250VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3528 | 250VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3529 | 250VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3530 | 250VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3531 | 250VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3532 | 250VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3533 | 250VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3534 | 250VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3535 | 250VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3536 | 250VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3537 | 250VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3538 | 250VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3539 | 250VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3540 | 250VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3541 | 250VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3542 | 250VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3543 | 250VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3544 | 250VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 1500W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3547 | 280VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3548 | 280VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3549 | 280VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3550 | 280VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3551 | 280VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3552 | 280VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3553 | 280VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3554 | 280VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3555 | 280VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3556 | 280VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3557 | 280VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3558 | 280VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3559 | 280VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3560 | 280VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3561 | 280VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3562 | 280VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3563 | 280VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3564 | 280VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 1500W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3567 | 300VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3568 | 300VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3569 | 300VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3570 | 300VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3571 | 300VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3572 | 300VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3573 | 300VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3574 | 300VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3575 | 300VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3576 | 300VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3577 | 300VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3578 | 300VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3579 | 300VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3580 | 300VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3581 | 300VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3582 | 300VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3583 | 300VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3584 | 300VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |

# 1500W 310VDC-400VDC

| 1500W 310VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3587 | 310VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3588 | 310VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3589 | 310VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3590 | 310VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3591 | 310VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3592 | 310VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3593 | 310VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3594 | 310VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3595 | 310VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3596 | 310VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3597 | 310VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3598 | 310VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3599 | 310VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3600 | 310VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3601 | 310VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3602 | 310VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3603 | 310VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3604 | 310VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 1500W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3607 | 350VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3608 | 350VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3609 | 350VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3610 | 350VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3611 | 350VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3612 | 350VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3613 | 350VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3614 | 350VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3615 | 350VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3616 | 350VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3617 | 350VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3618 | 350VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3619 | 350VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3620 | 350VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3621 | 350VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3622 | 350VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3623 | 350VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3624 | 350VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 1500W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3627 | 400VDC±15% | 12VDC±1-2% | 125A | 100A | 1500W | 750W | 440*300*110MM | 5/7KG |
| 3628 | 400VDC±15% | 24VDC±1-2% | 62.5A | 50A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3629 | 400VDC±15% | 36VDC±1-2% | 41.6A | 33A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3630 | 400VDC±15% | 48VDC±1-2% | 31A | 25A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3631 | 400VDC±15% | 60VDC±1-2% | 25A | 20A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3632 | 400VDC±15% | 72VDC±1-2% | 20.8A | 16.6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3633 | 400VDC±15% | 80VDC±1-2% | 18.7A | 15A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3634 | 400VDC±15% | 100VDC±1-2% | 15A | 12A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3635 | 400VDC±15% | 110VDC±1-2% | 13.6A | 10.9A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3636 | 400VDC±15% | 150VDC±1-2% | 10A | 8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3637 | 400VDC±15% | 200VDC±1-2% | 7.5A | 6A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3638 | 400VDC±15% | 220VDC±1-2% | 6.8A | 5.5A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3639 | 400VDC±15% | 250VDC±1-2% | 6A | 4.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3640 | 400VDC±15% | 280VDC±1-2% | 5.4A | 4.3A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3641 | 400VDC±15% | 300VDC±1-2% | 5A | 4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3642 | 400VDC±15% | 310VDC±1-2% | 4.8A | 3.8A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3643 | 400VDC±15% | 350VDC±1-2% | 4.3A | 3.4A | 1500W | 1200W | 440*300*110MM | 5/7KG |
| 3644 | 400VDC±15% | 400VDC±1-2% | 3.8A | 3A | 1500W | 1200W | 440*300*110MM | 5/7KG |

# 2000W 12VDC-36VDC

| 2000W 12VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3647 | 12VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3648 | 12VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3649 | 12VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3650 | 12VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3651 | 12VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3652 | 12VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3653 | 12VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3654 | 12VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3655 | 12VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3656 | 12VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3657 | 12VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3658 | 12VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3659 | 12VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3660 | 12VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3661 | 12VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3662 | 12VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3663 | 12VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3664 | 12VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 2000W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3667 | 24VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3668 | 24VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3669 | 24VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3670 | 24VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3671 | 24VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3672 | 24VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3673 | 24VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3674 | 24VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3675 | 24VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3676 | 24VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3677 | 24VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3678 | 24VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3679 | 24VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3680 | 24VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3681 | 24VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3682 | 24VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3683 | 24VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3684 | 24VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 2000W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3687 | 36VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3688 | 36VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3689 | 36VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3690 | 36VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3691 | 36VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3692 | 36VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3693 | 36VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3694 | 36VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3695 | 36VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3696 | 36VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3697 | 36VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3698 | 36VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3699 | 36VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3700 | 36VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3701 | 36VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3702 | 36VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3703 | 36VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3704 | 36VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |

# 2000W 48VDC-72VDC

| 2000W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3707 | 48VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3708 | 48VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3709 | 48VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3710 | 48VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3711 | 48VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3712 | 48VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3713 | 48VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3714 | 48VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3715 | 48VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3716 | 48VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3717 | 48VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3718 | 48VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3719 | 48VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3720 | 48VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3721 | 48VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3722 | 48VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3723 | 48VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3724 | 48VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 2000W 60VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3727 | 60VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3728 | 60VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3729 | 60VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3730 | 60VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3731 | 60VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3732 | 60VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3733 | 60VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3734 | 60VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3735 | 60VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3736 | 60VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3737 | 60VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3738 | 60VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3739 | 60VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3740 | 60VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3741 | 60VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3742 | 60VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3743 | 60VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3744 | 60VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 2000W 72VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3747 | 72VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3748 | 72VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3749 | 72VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3750 | 72VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3751 | 72VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3752 | 72VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3753 | 72VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3754 | 72VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3755 | 72VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3756 | 72VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3757 | 72VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3758 | 72VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3759 | 72VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3760 | 72VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3761 | 72VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3762 | 72VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3763 | 72VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3764 | 72VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |

# 2000W 80VDC-110VDC

| 2000W 80VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3767 | 80VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3768 | 80VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3769 | 80VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3770 | 80VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3771 | 80VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3772 | 80VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3773 | 80VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3774 | 80VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3775 | 80VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3776 | 80VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3777 | 80VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3778 | 80VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3779 | 80VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3780 | 80VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3781 | 80VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3782 | 80VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3783 | 80VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3784 | 80VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 2000W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3787 | 100VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3788 | 100VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3789 | 100VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3790 | 100VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3791 | 100VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3792 | 100VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3793 | 100VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3794 | 100VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3795 | 100VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3796 | 100VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3797 | 100VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3798 | 100VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3799 | 100VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3800 | 100VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3801 | 100VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3802 | 100VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3803 | 100VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3804 | 100VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 2000W 110VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3807 | 110VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3808 | 110VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3809 | 110VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3810 | 110VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3811 | 110VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3812 | 110VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3813 | 110VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3814 | 110VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3815 | 110VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3816 | 110VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3817 | 110VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3818 | 110VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3819 | 110VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3820 | 110VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3821 | 110VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3822 | 110VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3823 | 110VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3824 | 110VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |

# 2000W 150VDC-220VDC

| 2000W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3827 | 150VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3828 | 150VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3829 | 150VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3830 | 150VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3831 | 150VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3832 | 150VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3833 | 150VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3834 | 150VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3835 | 150VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3836 | 150VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3837 | 150VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3838 | 150VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3839 | 150VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3840 | 150VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3841 | 150VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3842 | 150VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3843 | 150VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3844 | 150VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 2000W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3847 | 200VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3848 | 200VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3849 | 200VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3850 | 200VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3851 | 200VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3852 | 200VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3853 | 200VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3854 | 200VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3855 | 200VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3856 | 200VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3857 | 200VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3858 | 200VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3859 | 200VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3860 | 200VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3861 | 200VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3862 | 200VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3863 | 200VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3864 | 200VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 2000W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3867 | 220VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3868 | 220VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3869 | 220VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3870 | 220VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3871 | 220VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3872 | 220VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3873 | 220VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3874 | 220VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3875 | 220VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3876 | 220VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3877 | 220VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3878 | 220VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3879 | 220VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3880 | 220VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3881 | 220VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3882 | 220VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3883 | 220VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3884 | 220VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |

# 2000W 250VDC-310VDC

| 2000W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3887 | 280VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3888 | 280VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3889 | 280VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3890 | 280VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3891 | 280VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3892 | 280VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3893 | 280VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3894 | 280VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3895 | 280VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3896 | 280VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3897 | 280VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3898 | 280VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3899 | 280VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3900 | 280VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3901 | 280VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3902 | 280VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3903 | 280VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3904 | 280VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 2000W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3907 | 300VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3908 | 300VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3909 | 300VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3910 | 300VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3911 | 300VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3912 | 300VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3913 | 300VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3914 | 300VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3915 | 300VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3916 | 300VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3917 | 300VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3918 | 300VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3919 | 300VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3920 | 300VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3921 | 300VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3922 | 300VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3923 | 300VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3924 | 300VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 2000W 310VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3927 | 310VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3928 | 310VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3929 | 310VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3930 | 310VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3931 | 310VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3932 | 310VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3933 | 310VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3934 | 310VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3935 | 310VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3936 | 310VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3937 | 310VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3938 | 310VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3939 | 310VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3940 | 310VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3941 | 310VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3942 | 310VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3943 | 310VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3944 | 310VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |

# 2000W 350VDC-400VDC / 3000W 12VDC

| 2000W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3947 | 350VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3948 | 350VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3949 | 350VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3950 | 350VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3951 | 350VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3952 | 350VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3953 | 350VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3954 | 350VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3955 | 350VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3956 | 350VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3957 | 350VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3958 | 350VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3959 | 350VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3960 | 350VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3961 | 350VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3962 | 350VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3963 | 350VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3964 | 350VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 2000W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3967 | 400VDC±15% | 12VDC±1-2% | 166.6A | 133.3A | 2000W | 1000W | 440*300*110MM | 5/7KG |
| 3968 | 400VDC±15% | 24VDC±1-2% | 83.3A | 66.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3969 | 400VDC±15% | 36VDC±1-2% | 55.5A | 44.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3970 | 400VDC±15% | 48VDC±1-2% | 41.6A | 33.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3971 | 400VDC±15% | 60VDC±1-2% | 33.3A | 26.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3972 | 400VDC±15% | 72VDC±1-2% | 27.7A | 22.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3973 | 400VDC±15% | 80VDC±1-2% | 25A | 20A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3974 | 400VDC±15% | 100VDC±1-2% | 20A | 16A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3975 | 400VDC±15% | 110VDC±1-2% | 18A | 14.5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3976 | 400VDC±15% | 150VDC±1-2% | 13.3A | 10.6A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3977 | 400VDC±15% | 200VDC±1-2% | 10A | 8A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3978 | 400VDC±15% | 220VDC±1-2% | 9A | 7.2A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3979 | 400VDC±15% | 250VDC±1-2% | 8A | 6.4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3980 | 400VDC±15% | 280VDC±1-2% | 7.1A | 5.7A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3981 | 400VDC±15% | 300VDC±1-2% | 6.6A | 5.3A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3982 | 400VDC±15% | 310VDC±1-2% | 6.4A | 5A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3983 | 400VDC±15% | 350VDC±1-2% | 5.7A | 4.57A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3984 | 400VDC±15% | 400VDC±1-2% | 5A | 4A | 2000W | 1600W | 440*300*110MM | 5/7KG |
| 3000W 12VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 3987 | 12VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 3988 | 12VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 3989 | 12VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 3990 | 12VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 3991 | 12VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 3992 | 12VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 3993 | 12VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 3994 | 12VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 3995 | 12VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 3996 | 12VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 3997 | 12VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 3998 | 12VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 3999 | 12VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4000 | 12VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4001 | 12VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4002 | 12VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4003 | 12VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4004 | 12VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 1500W | 440*300*110MM | 5/7KG |

# 3000W 24VDC-48VDC

| 3000W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4007 | 24VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4008 | 24VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4009 | 24VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4010 | 24VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4011 | 24VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4012 | 24VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4013 | 24VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4014 | 24VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4015 | 24VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4016 | 24VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4017 | 24VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4018 | 24VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4019 | 24VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4020 | 24VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4021 | 24VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4022 | 24VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4023 | 24VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4024 | 24VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 3000W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4027 | 36VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4028 | 36VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4029 | 36VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4030 | 36VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4031 | 36VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4032 | 36VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4033 | 36VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4034 | 36VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4035 | 36VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4036 | 36VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4037 | 36VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4038 | 36VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4039 | 36VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4040 | 36VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4041 | 36VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4042 | 36VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4043 | 36VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4044 | 36VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 3000W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4047 | 48VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4048 | 48VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4049 | 48VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4050 | 48VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4051 | 48VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4052 | 48VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4053 | 48VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4054 | 48VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4055 | 48VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4056 | 48VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4057 | 48VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4058 | 48VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4059 | 48VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4060 | 48VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4061 | 48VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4062 | 48VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4063 | 48VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4064 | 48VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |

# 3000W 60VDC-80VDC

| 3000W 60VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4067 | 60VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4068 | 60VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4069 | 60VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4070 | 60VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4071 | 60VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4072 | 60VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4073 | 60VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4074 | 60VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4075 | 60VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4076 | 60VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4077 | 60VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4078 | 60VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4079 | 60VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4080 | 60VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4081 | 60VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4082 | 60VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4083 | 60VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4084 | 60VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 3000W 72VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4087 | 72VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4088 | 72VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4089 | 72VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4090 | 72VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4091 | 72VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4092 | 72VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4093 | 72VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4094 | 72VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4095 | 72VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4096 | 72VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4097 | 72VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4098 | 72VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4099 | 72VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4100 | 72VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4101 | 72VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4102 | 72VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4103 | 72VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4104 | 72VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 3000W 80VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4107 | 80VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4108 | 80VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4109 | 80VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4110 | 80VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4111 | 80VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4112 | 80VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4113 | 80VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4114 | 80VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4115 | 80VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4116 | 80VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4117 | 80VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4118 | 80VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4119 | 80VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4120 | 80VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4121 | 80VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4122 | 80VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4123 | 80VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4124 | 80VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |

# 3000W 100VDC-150VDC

| 3000W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4127 | 100VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4128 | 100VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4129 | 100VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4130 | 100VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4131 | 100VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4132 | 100VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4133 | 100VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4134 | 100VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4135 | 100VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4136 | 100VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4137 | 100VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4138 | 100VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4139 | 100VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4140 | 100VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4141 | 100VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4142 | 100VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4143 | 100VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4144 | 100VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 3000W 110VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4147 | 110VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4148 | 110VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4149 | 110VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4150 | 110VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4151 | 110VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4152 | 110VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4153 | 110VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4154 | 110VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4155 | 110VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4156 | 110VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4157 | 110VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4158 | 110VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4159 | 110VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4160 | 110VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4161 | 110VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4162 | 110VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4163 | 110VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4164 | 110VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 3000W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4167 | 150VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4168 | 150VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4169 | 150VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4170 | 150VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4171 | 150VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4172 | 150VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4173 | 150VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4174 | 150VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4175 | 150VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4176 | 150VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4177 | 150VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4178 | 150VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4179 | 150VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4180 | 150VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4181 | 150VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4182 | 150VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4183 | 150VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4184 | 150VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |

# 3000W 200VDC-250VDC

| 3000W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4187 | 200VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4188 | 200VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4189 | 200VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4190 | 200VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4191 | 200VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4192 | 200VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4193 | 200VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4194 | 200VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4195 | 200VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4196 | 200VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4197 | 200VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4198 | 200VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4199 | 200VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4200 | 200VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4201 | 200VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4202 | 200VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4203 | 200VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4204 | 200VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 3000W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4207 | 220VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4208 | 220VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4209 | 220VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4210 | 220VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4211 | 220VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4212 | 220VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4213 | 220VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4214 | 220VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4215 | 220VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4216 | 220VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4217 | 220VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4218 | 220VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4219 | 220VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4220 | 220VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4221 | 220VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4222 | 220VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4223 | 220VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4224 | 220VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 3000W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4227 | 250VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4228 | 250VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4229 | 250VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4230 | 250VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4231 | 250VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4232 | 250VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4233 | 250VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4234 | 250VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4235 | 250VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4236 | 250VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4237 | 250VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4238 | 250VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4239 | 250VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4240 | 250VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4241 | 250VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4242 | 250VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4243 | 250VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4244 | 250VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |

# 3000W 280VDC-310VDC

| 3000W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4247 | 280VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4248 | 280VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4249 | 280VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4250 | 280VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4251 | 280VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4252 | 280VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4253 | 280VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4254 | 280VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4255 | 280VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4256 | 280VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4257 | 280VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4258 | 280VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4259 | 280VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4260 | 280VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4261 | 280VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4262 | 280VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4263 | 280VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4264 | 280VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 3000W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4267 | 300VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4268 | 300VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4269 | 300VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4270 | 300VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4271 | 300VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4272 | 300VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4273 | 300VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4274 | 300VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4275 | 300VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4276 | 300VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4277 | 300VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4278 | 300VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4279 | 300VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4280 | 300VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4281 | 300VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4282 | 300VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4283 | 300VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4284 | 300VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 3000W 310VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4287 | 310VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4288 | 310VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4289 | 310VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4290 | 310VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4291 | 310VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4292 | 310VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4293 | 310VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4294 | 310VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4295 | 310VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4296 | 310VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4297 | 310VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4298 | 310VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4299 | 310VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4300 | 310VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4301 | 310VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4302 | 310VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4303 | 310VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4304 | 310VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |

# 3000W 350VDC-400VDC / 4000W 24VDC

| 3000W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4307 | 350VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4308 | 350VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4309 | 350VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4310 | 350VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4311 | 350VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4312 | 350VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4313 | 350VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4314 | 350VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4315 | 350VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4316 | 350VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4317 | 350VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4318 | 350VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4319 | 350VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4320 | 350VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4321 | 350VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4322 | 350VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4323 | 350VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4324 | 350VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 3000W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4327 | 400VDC±15% | 12VDC±1-2% | 250A | 100A | 3000W | 1500W | 440*300*110MM | 5/7KG |
| 4328 | 400VDC±15% | 24VDC±1-2% | 125A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4329 | 400VDC±15% | 36VDC±1-2% | 83.3A | 200A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4330 | 400VDC±15% | 48VDC±1-2% | 62.5A | 100A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4331 | 400VDC±15% | 60VDC±1-2% | 50A | 66.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4332 | 400VDC±15% | 72VDC±1-2% | 41.6A | 50A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4333 | 400VDC±15% | 80VDC±1-2% | 37.5A | 40A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4334 | 400VDC±15% | 100VDC±1-2% | 30A | 33.3A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4335 | 400VDC±15% | 110VDC±1-2% | 27A | 30A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4336 | 400VDC±15% | 150VDC±1-2% | 20A | 24A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4337 | 400VDC±15% | 200VDC±1-2% | 15A | 21.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4338 | 400VDC±15% | 220VDC±1-2% | 13.6A | 16A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4339 | 400VDC±15% | 250VDC±1-2% | 12A | 12A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4340 | 400VDC±15% | 280VDC±1-2% | 10.7A | 10.9A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4341 | 400VDC±15% | 300VDC±1-2% | 10A | 9.6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4342 | 400VDC±15% | 310VDC±1-2% | 9.6A | 7.7A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4343 | 400VDC±15% | 350VDC±1-2% | 8.57A | 6.8A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4344 | 400VDC±15% | 400VDC±1-2% | 7.5A | 6A | 3000W | 2400W | 440*300*110MM | 5/7KG |
| 4000W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4347 | 24VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4348 | 24VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4349 | 24VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4350 | 24VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4351 | 24VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4352 | 24VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4353 | 24VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4354 | 24VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4355 | 24VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4356 | 24VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4357 | 24VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4358 | 24VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4359 | 24VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4360 | 24VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4361 | 24VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4362 | 24VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4363 | 24VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4364 | 24VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4365 | 24VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4366 | 24VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |

# 4000W 36VDC-60VDC

| 4000W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4369 | 36VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4370 | 36VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4371 | 36VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4372 | 36VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4373 | 36VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4374 | 36VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4375 | 36VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4376 | 36VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4377 | 36VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4378 | 36VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4379 | 36VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4380 | 36VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4381 | 36VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4382 | 36VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4383 | 36VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4384 | 36VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4385 | 36VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4386 | 36VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4387 | 36VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4388 | 36VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4000W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4391 | 48VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4392 | 48VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4393 | 48VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4394 | 48VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4395 | 48VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4396 | 48VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4397 | 48VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4398 | 48VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4399 | 48VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4400 | 48VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4401 | 48VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4402 | 48VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4403 | 48VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4404 | 48VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4405 | 48VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4406 | 48VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4407 | 48VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4408 | 48VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4409 | 48VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4410 | 48VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4000W 60VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4413 | 60VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4414 | 60VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4415 | 60VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4416 | 60VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4417 | 60VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4418 | 60VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4419 | 60VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4420 | 60VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4421 | 60VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4422 | 60VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4423 | 60VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4424 | 60VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4425 | 60VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4426 | 60VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4427 | 60VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4428 | 60VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4429 | 60VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4430 | 60VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4431 | 60VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4432 | 60VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |

# 4000W 72VDC-100VDC

| 4000W 72VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4435 | 72VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4436 | 72VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4437 | 72VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4438 | 72VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4439 | 72VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4440 | 72VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4441 | 72VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4442 | 72VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4443 | 72VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4444 | 72VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4445 | 72VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4446 | 72VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4447 | 72VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4448 | 72VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4449 | 72VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4450 | 72VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4451 | 72VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4452 | 72VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4453 | 72VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4454 | 72VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4000W 80VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4457 | 80VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4458 | 80VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4459 | 80VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4460 | 80VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4461 | 80VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4462 | 80VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4463 | 80VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4464 | 80VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4465 | 80VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4466 | 80VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4467 | 80VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4468 | 80VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4469 | 80VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4470 | 80VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4471 | 80VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4472 | 80VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4473 | 80VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4474 | 80VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4475 | 80VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4476 | 80VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4000W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4479 | 100VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4480 | 100VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4481 | 100VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4482 | 100VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4483 | 100VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4484 | 100VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4485 | 100VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4486 | 100VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4487 | 100VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4488 | 100VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4489 | 100VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4490 | 100VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4491 | 100VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4492 | 100VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4493 | 100VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4494 | 100VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4495 | 100VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4496 | 100VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4497 | 100VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4498 | 100VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |

# 4000W 110VDC-200VDC

| 4000W 110VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4501 | 110VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4502 | 110VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4503 | 110VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4504 | 110VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4505 | 110VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4506 | 110VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4507 | 110VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4508 | 110VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4509 | 110VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4510 | 110VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4511 | 110VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4512 | 110VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4513 | 110VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4514 | 110VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4515 | 110VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4516 | 110VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4517 | 110VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4518 | 110VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4519 | 110VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4520 | 110VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4000W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4523 | 150VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4524 | 150VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4525 | 150VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4526 | 150VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4527 | 150VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4528 | 150VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4529 | 150VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4530 | 150VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4531 | 150VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4532 | 150VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4533 | 150VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4534 | 150VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4535 | 150VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4536 | 150VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4537 | 150VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4538 | 150VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4539 | 150VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4540 | 150VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4541 | 150VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4542 | 150VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4000W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4545 | 200VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4546 | 200VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4547 | 200VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4548 | 200VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4549 | 200VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4550 | 200VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4551 | 200VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4552 | 200VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4553 | 200VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4554 | 200VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4555 | 200VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4556 | 200VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4557 | 200VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4558 | 200VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4559 | 200VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4560 | 200VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4561 | 200VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4562 | 200VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4563 | 200VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4564 | 200VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |

# 4000W 220VDC-280VDC

| 4000W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4567 | 220VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4568 | 220VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4569 | 220VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4570 | 220VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4571 | 220VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4572 | 220VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4573 | 220VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4574 | 220VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4575 | 220VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4576 | 220VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4577 | 220VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4578 | 220VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4579 | 220VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4580 | 220VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4581 | 220VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4582 | 220VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4583 | 220VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4584 | 220VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4585 | 220VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4586 | 220VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4000W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4589 | 250VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4590 | 250VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4591 | 250VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4592 | 250VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4593 | 250VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4594 | 250VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4595 | 250VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4596 | 250VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4597 | 250VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4598 | 250VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4599 | 250VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4600 | 250VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4601 | 250VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4602 | 250VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4603 | 250VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4604 | 250VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4605 | 250VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4606 | 250VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4607 | 250VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4608 | 250VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4000W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4611 | 280VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4612 | 280VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4613 | 280VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4614 | 280VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4615 | 280VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4616 | 280VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4617 | 280VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4618 | 280VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4619 | 280VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4620 | 280VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4621 | 280VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4622 | 280VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4623 | 280VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4624 | 280VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4625 | 280VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4626 | 280VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4627 | 280VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4628 | 280VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4629 | 280VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4630 | 280VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |

# 4000W 300VDC-350VDC

| 4000W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4633 | 300VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4634 | 300VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4635 | 300VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4636 | 300VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4637 | 300VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4638 | 300VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4639 | 300VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4640 | 300VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4641 | 300VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4642 | 300VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4643 | 300VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4644 | 300VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4645 | 300VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4646 | 300VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4647 | 300VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4648 | 300VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4649 | 300VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4650 | 300VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4651 | 300VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4652 | 300VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4000W 310VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4655 | 310VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4656 | 310VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4657 | 310VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4658 | 310VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4659 | 310VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4660 | 310VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4661 | 310VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4662 | 310VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4663 | 310VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4664 | 310VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4665 | 310VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4666 | 310VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4667 | 310VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4668 | 310VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4669 | 310VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4670 | 310VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4671 | 310VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4672 | 310VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4673 | 310VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4674 | 310VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4000W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4677 | 350VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4678 | 350VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4679 | 350VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4680 | 350VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4681 | 350VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4682 | 350VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4683 | 350VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4684 | 350VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4685 | 350VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4686 | 350VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4687 | 350VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4688 | 350VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4689 | 350VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4690 | 350VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4691 | 350VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4692 | 350VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4693 | 350VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4694 | 350VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4695 | 350VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4696 | 350VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |

# 4000W 400VDC-500VDC

| 4000W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4699 | 400VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4700 | 400VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4701 | 400VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4702 | 400VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4703 | 400VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4704 | 400VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4705 | 400VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4706 | 400VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4707 | 400VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4708 | 400VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4709 | 400VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4710 | 400VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4711 | 400VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4712 | 400VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4713 | 400VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4714 | 400VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4715 | 400VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4716 | 400VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4717 | 400VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4718 | 400VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4000W 450VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4721 | 450VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4722 | 450VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4723 | 450VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4724 | 450VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4725 | 450VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4726 | 450VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4727 | 450VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4728 | 450VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4729 | 450VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4730 | 450VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4731 | 450VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4732 | 450VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4733 | 450VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4734 | 450VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4735 | 450VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4736 | 450VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4737 | 450VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4738 | 450VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4739 | 450VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4740 | 450VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4000W 500VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4743 | 500VDC±15% | 12VDC±1-2% | 333.3A | 266.6A | 4000W | 2000W | 440*300*110MM | 5/7KG |
| 4744 | 500VDC±15% | 24VDC±1-2% | 166.6A | 133.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4745 | 500VDC±15% | 36VDC±1-2% | 111.1A | 88.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4746 | 500VDC±15% | 48VDC±1-2% | 83.3A | 66.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4747 | 500VDC±15% | 60VDC±1-2% | 66.6A | 53.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4748 | 500VDC±15% | 72VDC±1-2% | 55.5A | 44.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4749 | 500VDC±15% | 80VDC±1-2% | 50A | 40A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4750 | 500VDC±15% | 100VDC±1-2% | 40A | 32A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4751 | 500VDC±15% | 110VDC±1-2% | 36A | 29A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4752 | 500VDC±15% | 150VDC±1-2% | 26.6A | 21.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4753 | 500VDC±15% | 200VDC±1-2% | 20A | 16A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4754 | 500VDC±15% | 220VDC±1-2% | 18A | 14.5A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4755 | 500VDC±15% | 250VDC±1-2% | 16A | 12.8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4756 | 500VDC±15% | 280VDC±1-2% | 14.2A | 11.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4757 | 500VDC±15% | 300VDC±1-2% | 13.3A | 10.6A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4758 | 500VDC±15% | 310VDC±1-2% | 12.9A | 10.3A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4759 | 500VDC±15% | 350VDC±1-2% | 11.4A | 9.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4760 | 500VDC±15% | 400VDC±1-2% | 10A | 8A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4761 | 500VDC±15% | 450VDC±1-2% | 8.8A | 7.1A | 4000W | 3200W | 440*300*110MM | 5/7KG |
| 4762 | 500VDC±15% | 500VDC±1-2% | 8A | 6.4A | 4000W | 3200W | 440*300*110MM | 5/7KG |

# 5000W 12VDC-36VDC

| 5000W 12VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4765 | 12VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4766 | 12VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4767 | 12VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4768 | 12VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4769 | 12VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4770 | 12VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4771 | 12VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4772 | 12VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4773 | 12VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4774 | 12VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4775 | 12VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4776 | 12VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4777 | 12VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4778 | 12VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4779 | 12VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4780 | 12VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4781 | 12VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4782 | 12VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4783 | 12VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4784 | 12VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 5000W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4787 | 24VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4788 | 24VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4789 | 24VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4790 | 24VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4791 | 24VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4792 | 24VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4793 | 24VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4794 | 24VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4795 | 24VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4796 | 24VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4797 | 24VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4798 | 24VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4799 | 24VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4800 | 24VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4801 | 24VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4802 | 24VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4803 | 24VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4804 | 24VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4805 | 24VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4806 | 24VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4809 | 36VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4810 | 36VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4811 | 36VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4812 | 36VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4813 | 36VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4814 | 36VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4815 | 36VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4816 | 36VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4817 | 36VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4818 | 36VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4819 | 36VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4820 | 36VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4821 | 36VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4822 | 36VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4823 | 36VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4824 | 36VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4825 | 36VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4826 | 36VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4827 | 36VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4828 | 36VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |

# 5000W 48VDC-72VDC

| 5000W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4831 | 48VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4832 | 48VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4833 | 48VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4834 | 48VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4835 | 48VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4836 | 48VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4837 | 48VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4838 | 48VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4839 | 48VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4840 | 48VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4841 | 48VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4842 | 48VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4843 | 48VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4844 | 48VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4845 | 48VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4846 | 48VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4847 | 48VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4848 | 48VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4849 | 48VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4850 | 48VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000W 60VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4853 | 60VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4854 | 60VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4855 | 60VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4856 | 60VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4857 | 60VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4858 | 60VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4859 | 60VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4860 | 60VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4861 | 60VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4862 | 60VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4863 | 60VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4864 | 60VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4865 | 60VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4866 | 60VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4867 | 60VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4868 | 60VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4869 | 60VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4870 | 60VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4871 | 60VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4872 | 60VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000W 72VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4875 | 72VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4876 | 72VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4877 | 72VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4878 | 72VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4879 | 72VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4880 | 72VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4881 | 72VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4882 | 72VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4883 | 72VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4884 | 72VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4885 | 72VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4886 | 72VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4887 | 72VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4888 | 72VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4889 | 72VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4890 | 72VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4891 | 72VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4892 | 72VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4893 | 72VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4894 | 72VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |

# 5000W 80VDC-110VDC

| 5000W 80VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4897 | 80VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4898 | 80VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4899 | 80VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4900 | 80VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4901 | 80VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4902 | 80VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4903 | 80VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4904 | 80VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4905 | 80VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4906 | 80VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4907 | 80VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4908 | 80VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4909 | 80VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4910 | 80VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4911 | 80VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4912 | 80VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4913 | 80VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4914 | 80VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4915 | 80VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4916 | 80VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4919 | 100VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4920 | 100VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4921 | 100VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4922 | 100VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4923 | 100VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4924 | 100VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4925 | 100VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4926 | 100VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4927 | 100VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4928 | 100VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4929 | 100VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4930 | 100VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4931 | 100VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4932 | 100VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4933 | 100VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4934 | 100VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4935 | 100VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4936 | 100VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4937 | 100VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4938 | 100VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000W 110VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4941 | 110VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4942 | 110VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4943 | 110VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4944 | 110VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4945 | 110VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4946 | 110VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4947 | 110VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4948 | 110VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4949 | 110VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4950 | 110VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4951 | 110VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4952 | 110VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4953 | 110VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4954 | 110VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4955 | 110VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4956 | 110VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4957 | 110VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4958 | 110VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4959 | 110VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4960 | 110VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |

# 5000W 150VDC-220VDC

| 5000W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4963 | 150VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4964 | 150VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4965 | 150VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4966 | 150VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4967 | 150VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4968 | 150VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4969 | 150VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4970 | 150VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4971 | 150VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4972 | 150VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4973 | 150VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4974 | 150VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4975 | 150VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4976 | 150VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4977 | 150VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4978 | 150VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4979 | 150VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4980 | 150VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4981 | 150VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4982 | 150VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 4985 | 200VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 4986 | 200VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4987 | 200VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4988 | 200VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4989 | 200VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4990 | 200VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4991 | 200VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4992 | 200VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4993 | 200VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4994 | 200VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4995 | 200VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4996 | 200VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4997 | 200VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4998 | 200VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 4999 | 200VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000 | 200VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5001 | 200VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5002 | 200VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5003 | 200VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5004 | 200VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5007 | 220VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 5008 | 220VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5009 | 220VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5010 | 220VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5011 | 220VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5012 | 220VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5013 | 220VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5014 | 220VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5015 | 220VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5016 | 220VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5017 | 220VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5018 | 220VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5019 | 220VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5020 | 220VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5021 | 220VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5022 | 220VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5023 | 220VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5024 | 220VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5025 | 220VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5026 | 220VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |

# 5000W 250VDC-300VDC

| 5000W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5029 | 250VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 5030 | 250VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5031 | 250VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5032 | 250VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5033 | 250VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5034 | 250VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5035 | 250VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5036 | 250VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5037 | 250VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5038 | 250VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5039 | 250VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5040 | 250VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5041 | 250VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5042 | 250VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5043 | 250VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5044 | 250VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5045 | 250VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5046 | 250VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5047 | 250VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5048 | 250VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5051 | 280VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 5052 | 280VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5053 | 280VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5054 | 280VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5055 | 280VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5056 | 280VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5057 | 280VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5058 | 280VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5059 | 280VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5060 | 280VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5061 | 280VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5062 | 280VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5063 | 280VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5064 | 280VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5065 | 280VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5066 | 280VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5067 | 280VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5068 | 280VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5069 | 280VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5070 | 280VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5073 | 300VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 5074 | 300VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5075 | 300VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5076 | 300VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5077 | 300VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5078 | 300VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5079 | 300VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5080 | 300VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5081 | 300VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5082 | 300VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5083 | 300VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5084 | 300VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5085 | 300VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5086 | 300VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5087 | 300VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5088 | 300VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5089 | 300VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5090 | 300VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5091 | 300VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5092 | 300VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |

# 5000W 310VDC-400VDC

| 5000W 310VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5095 | 310VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 5096 | 310VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5097 | 310VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5098 | 310VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5099 | 310VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5100 | 310VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5101 | 310VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5102 | 310VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5103 | 310VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5104 | 310VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5105 | 310VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5106 | 310VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5107 | 310VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5108 | 310VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5109 | 310VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5110 | 310VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5111 | 310VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5112 | 310VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5113 | 310VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5114 | 310VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5117 | 350VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 5118 | 350VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5119 | 350VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5120 | 350VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5121 | 350VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5122 | 350VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5123 | 350VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5124 | 350VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5125 | 350VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5126 | 350VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5127 | 350VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5128 | 350VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5129 | 350VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5130 | 350VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5131 | 350VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5132 | 350VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5133 | 350VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5134 | 350VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5135 | 350VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5136 | 350VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5139 | 400VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 5140 | 400VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5141 | 400VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5142 | 400VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5143 | 400VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5144 | 400VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5145 | 400VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5146 | 400VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5147 | 400VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5148 | 400VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5149 | 400VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5150 | 400VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5151 | 400VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5152 | 400VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5153 | 400VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5154 | 400VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5155 | 400VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5156 | 400VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5157 | 400VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5158 | 400VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |

# 5000W 450VDC-500VDC / 6000W 24VDC

| 5000W 450VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5161 | 450VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 5162 | 450VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5163 | 450VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5164 | 450VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5165 | 450VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5166 | 450VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5167 | 450VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5168 | 450VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5169 | 450VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5170 | 450VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5171 | 450VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5172 | 450VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5173 | 450VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5174 | 450VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5175 | 450VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5176 | 450VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5177 | 450VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5178 | 450VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5179 | 450VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5180 | 450VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5000W 500VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5183 | 500VDC±15% | 12VDC±1-2% | 416A | 333A | 5000W | 2500W | 440*350*130MM | 6/8KG |
| 5184 | 500VDC±15% | 24VDC±1-2% | 208A | 166A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5185 | 500VDC±15% | 36VDC±1-2% | 138A | 111A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5186 | 500VDC±15% | 48VDC±1-2% | 104A | 83.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5187 | 500VDC±15% | 60VDC±1-2% | 83A | 66.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5188 | 500VDC±15% | 72VDC±1-2% | 69A | 55.5A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5189 | 500VDC±15% | 80VDC±1-2% | 62.5A | 50A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5190 | 500VDC±15% | 100VDC±1-2% | 50A | 40A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5191 | 500VDC±15% | 110VDC±1-2% | 45.4A | 36A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5192 | 500VDC±15% | 150VDC±1-2% | 33.3A | 26.6A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5193 | 500VDC±15% | 200VDC±1-2% | 25A | 20A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5194 | 500VDC±15% | 220VDC±1-2% | 22.7A | 18A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5195 | 500VDC±15% | 250VDC±1-2% | 20A | 16A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5196 | 500VDC±15% | 280VDC±1-2% | 17.8A | 14.2A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5197 | 500VDC±15% | 300VDC±1-2% | 16.6A | 13.3A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5198 | 500VDC±15% | 310VDC±1-2% | 16A | 12.9A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5199 | 500VDC±15% | 350VDC±1-2% | 14.2A | 11.4A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5200 | 500VDC±15% | 400VDC±1-2% | 12.5A | 10A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5201 | 500VDC±15% | 450VDC±1-2% | 11A | 8.8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 5202 | 500VDC±15% | 500VDC±1-2% | 10A | 8A | 5000W | 4000W | 440*350*130MM | 6/8KG |
| 6000W 24VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5205 | 24VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5206 | 24VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5207 | 24VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5208 | 24VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5209 | 24VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5210 | 24VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5211 | 24VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5212 | 24VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5213 | 24VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5214 | 24VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5215 | 24VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5216 | 24VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5217 | 24VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5218 | 24VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5219 | 24VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5220 | 24VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5221 | 24VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5222 | 24VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5223 | 24VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5224 | 24VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |

# 6000W 36VDC-60VDC

| 6000W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5227 | 36VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5228 | 36VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5229 | 36VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5230 | 36VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5231 | 36VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5232 | 36VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5233 | 36VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5234 | 36VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5235 | 36VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5236 | 36VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5237 | 36VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5238 | 36VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5239 | 36VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5240 | 36VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5241 | 36VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5242 | 36VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5243 | 36VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5244 | 36VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5245 | 36VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5246 | 36VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 6000W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5249 | 48VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5250 | 48VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5251 | 48VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5252 | 48VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5253 | 48VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5254 | 48VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5255 | 48VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5256 | 48VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5257 | 48VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5258 | 48VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5259 | 48VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5260 | 48VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5261 | 48VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5262 | 48VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5263 | 48VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5264 | 48VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5265 | 48VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5266 | 48VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5267 | 48VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5268 | 48VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 6000W 60VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5271 | 60VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5272 | 60VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5273 | 60VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5274 | 60VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5275 | 60VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5276 | 60VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5277 | 60VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5278 | 60VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5279 | 60VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5280 | 60VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5281 | 60VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5282 | 60VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5283 | 60VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5284 | 60VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5285 | 60VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5286 | 60VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5287 | 60VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5288 | 60VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5289 | 60VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5290 | 60VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |

# 6000W 72VDC-100VDC

| 6000W 72VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5293 | 72VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5294 | 72VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5295 | 72VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5296 | 72VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5297 | 72VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5298 | 72VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5299 | 72VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5300 | 72VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5301 | 72VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5302 | 72VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5303 | 72VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5304 | 72VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5305 | 72VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5306 | 72VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5307 | 72VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5308 | 72VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5309 | 72VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5310 | 72VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5311 | 72VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5312 | 72VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 6000W 80VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5315 | 80VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5316 | 80VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5317 | 80VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5318 | 80VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5319 | 80VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5320 | 80VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5321 | 80VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5322 | 80VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5323 | 80VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5324 | 80VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5325 | 80VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5326 | 80VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5327 | 80VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5328 | 80VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5329 | 80VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5330 | 80VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5331 | 80VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5332 | 80VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5333 | 80VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5334 | 80VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 6000W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5337 | 100VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5338 | 100VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5339 | 100VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5340 | 100VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5341 | 100VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5342 | 100VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5343 | 100VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5344 | 100VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5345 | 100VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5346 | 100VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5347 | 100VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5348 | 100VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5349 | 100VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5350 | 100VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5351 | 100VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5352 | 100VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5353 | 100VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5354 | 100VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5355 | 100VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5356 | 100VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |

# 6000W 110VDC-200VDC

| 6000W 110VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5359 | 110VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5360 | 110VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5361 | 110VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5362 | 110VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5363 | 110VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5364 | 110VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5365 | 110VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5366 | 110VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5367 | 110VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5368 | 110VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5369 | 110VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5370 | 110VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5371 | 110VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5372 | 110VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5373 | 110VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5374 | 110VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5375 | 110VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5376 | 110VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5377 | 110VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5378 | 110VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 6000W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5381 | 150VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5382 | 150VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5383 | 150VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5384 | 150VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5385 | 150VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5386 | 150VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5387 | 150VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5388 | 150VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5389 | 150VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5390 | 150VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5391 | 150VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5392 | 150VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5393 | 150VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5394 | 150VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5395 | 150VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5396 | 150VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5397 | 150VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5398 | 150VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5399 | 150VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5400 | 150VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 6000W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5403 | 200VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5404 | 200VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5405 | 200VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5406 | 200VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5407 | 200VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5408 | 200VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5409 | 200VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5410 | 200VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5411 | 200VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5412 | 200VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5413 | 200VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5414 | 200VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5415 | 200VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5416 | 200VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5417 | 200VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5418 | 200VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5419 | 200VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5420 | 200VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5421 | 200VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5422 | 200VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |

| 6000W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5425 | 220VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5426 | 220VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5427 | 220VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5428 | 220VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5429 | 220VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5430 | 220VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5431 | 220VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5432 | 220VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5433 | 220VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5434 | 220VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5435 | 220VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5436 | 220VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5437 | 220VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5438 | 220VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5439 | 220VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5440 | 220VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5441 | 220VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5442 | 220VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5443 | 220VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5444 | 220VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 6000W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5447 | 250VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5448 | 250VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5449 | 250VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5450 | 250VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5451 | 250VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5452 | 250VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5453 | 250VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5454 | 250VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5455 | 250VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5456 | 250VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5457 | 250VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5458 | 250VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5459 | 250VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5460 | 250VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5461 | 250VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5462 | 250VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5463 | 250VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5464 | 250VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5465 | 250VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5466 | 250VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |

# 6000W 280VDC-310VDC

| 6000W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5469 | 280VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5470 | 280VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5471 | 280VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5472 | 280VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5473 | 280VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5474 | 280VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5475 | 280VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5476 | 280VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5477 | 280VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5478 | 280VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5479 | 280VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5480 | 280VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5481 | 280VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5482 | 280VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5483 | 280VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5484 | 280VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5485 | 280VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5486 | 280VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5487 | 280VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5488 | 280VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 6000W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5491 | 300VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5492 | 300VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5493 | 300VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5494 | 300VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5495 | 300VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5496 | 300VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5497 | 300VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5498 | 300VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5499 | 300VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5500 | 300VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5501 | 300VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5502 | 300VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5503 | 300VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5504 | 300VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5505 | 300VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5506 | 300VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5507 | 300VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5508 | 300VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5509 | 300VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5510 | 300VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 6000W 310VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5513 | 310VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5514 | 310VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5515 | 310VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5516 | 310VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5517 | 310VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5518 | 310VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5519 | 310VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5520 | 310VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5521 | 310VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5522 | 310VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5523 | 310VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5524 | 310VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5525 | 310VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5526 | 310VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5527 | 310VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5528 | 310VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5529 | 310VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5530 | 310VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5531 | 310VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5532 | 310VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |

# 6000W 350VDC-450VDC

| 6000W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5535 | 350VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5536 | 350VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5537 | 350VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5538 | 350VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5539 | 350VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5540 | 350VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5541 | 350VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5542 | 350VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5543 | 350VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5544 | 350VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5545 | 350VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5546 | 350VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5547 | 350VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5548 | 350VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5549 | 350VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5550 | 350VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5551 | 350VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5552 | 350VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5553 | 350VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5554 | 350VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 6000W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5557 | 400VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5558 | 400VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5559 | 400VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5560 | 400VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5561 | 400VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5562 | 400VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5563 | 400VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5564 | 400VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5565 | 400VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5566 | 400VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5567 | 400VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5568 | 400VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5569 | 400VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5570 | 400VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5571 | 400VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5572 | 400VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5573 | 400VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5574 | 400VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5575 | 400VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5576 | 400VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 6000W 450VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5579 | 450VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5580 | 450VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5581 | 450VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5582 | 450VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5583 | 450VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5584 | 450VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5585 | 450VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5586 | 450VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5587 | 450VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5588 | 450VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5589 | 450VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5590 | 450VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5591 | 450VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5592 | 450VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5593 | 450VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5594 | 450VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5595 | 450VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5596 | 450VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5597 | 450VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5598 | 450VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |

# 6000W 500VDC / 7500W 36VDC-48VDC

| 6000W 500VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5601 | 500VDC±15% | 12VDC±1-2% | 500A | 400A | 6000W | 3000W | 440*350*130MM | 6/8KG |
| 5602 | 500VDC±15% | 24VDC±1-2% | 250A | 200A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5603 | 500VDC±15% | 36VDC±1-2% | 166A | 133A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5604 | 500VDC±15% | 48VDC±1-2% | 125A | 100A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5605 | 500VDC±15% | 60VDC±1-2% | 100A | 80A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5606 | 500VDC±15% | 72VDC±1-2% | 83A | 66A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5607 | 500VDC±15% | 80VDC±1-2% | 75A | 60A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5608 | 500VDC±15% | 100VDC±1-2% | 60A | 48A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5609 | 500VDC±15% | 110VDC±1-2% | 54A | 43A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5610 | 500VDC±15% | 150VDC±1-2% | 40A | 32A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5611 | 500VDC±15% | 200VDC±1-2% | 30A | 24A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5612 | 500VDC±15% | 220VDC±1-2% | 27A | 21.8A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5613 | 500VDC±15% | 250VDC±1-2% | 24A | 19A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5614 | 500VDC±15% | 280VDC±1-2% | 21A | 17A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5615 | 500VDC±15% | 300VDC±1-2% | 20A | 16A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5616 | 500VDC±15% | 310VDC±1-2% | 19A | 15A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5617 | 500VDC±15% | 350VDC±1-2% | 17A | 13.7A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5618 | 500VDC±15% | 400VDC±1-2% | 15A | 12A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5619 | 500VDC±15% | 450VDC±1-2% | 13.3A | 10.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 5620 | 500VDC±15% | 500VDC±1-2% | 12A | 9.6A | 6000W | 4800W | 440*350*130MM | 6/8KG |
| 7500W 36VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5623 | 36VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5624 | 36VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5625 | 36VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5626 | 36VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5627 | 36VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5628 | 36VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5629 | 36VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5630 | 36VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5631 | 36VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5632 | 36VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5633 | 36VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5634 | 36VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5635 | 36VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5636 | 36VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5637 | 36VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5638 | 36VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5639 | 36VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5640 | 36VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 7500W 48VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5643 | 48VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5644 | 48VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5645 | 48VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5646 | 48VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5647 | 48VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5648 | 48VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5649 | 48VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5650 | 48VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5651 | 48VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5652 | 48VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5653 | 48VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5654 | 48VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5655 | 48VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5656 | 48VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5657 | 48VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5658 | 48VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5659 | 48VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5660 | 48VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |

# 7500W 60VDC-80VDC

| 7500W 60VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5663 | 60VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5664 | 60VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5665 | 60VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5666 | 60VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5667 | 60VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5668 | 60VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5669 | 60VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5670 | 60VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5671 | 60VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5672 | 60VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5673 | 60VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5674 | 60VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5675 | 60VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5676 | 60VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5677 | 60VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5678 | 60VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5679 | 60VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5680 | 60VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 7500W 72VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5683 | 72VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5684 | 72VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5685 | 72VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5686 | 72VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5687 | 72VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5688 | 72VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5689 | 72VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5690 | 72VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5691 | 72VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5692 | 72VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5693 | 72VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5694 | 72VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5695 | 72VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5696 | 72VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5697 | 72VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5698 | 72VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5699 | 72VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5700 | 72VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 7500W 80VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5703 | 80VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5704 | 80VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5705 | 80VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5706 | 80VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5707 | 80VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5708 | 80VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5709 | 80VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5710 | 80VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5711 | 80VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5712 | 80VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5713 | 80VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5714 | 80VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5715 | 80VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5716 | 80VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5717 | 80VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5718 | 80VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5719 | 80VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5720 | 80VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |

# 7500W 100VDC-150VDC

| 7500W 100VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5723 | 100VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5724 | 100VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5725 | 100VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5726 | 100VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5727 | 100VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5728 | 100VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5729 | 100VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5730 | 100VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5731 | 100VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5732 | 100VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5733 | 100VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5734 | 100VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5735 | 100VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5736 | 100VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5737 | 100VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5738 | 100VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5739 | 100VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5740 | 100VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 7500W 110VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5743 | 110VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5744 | 110VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5745 | 110VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5746 | 110VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5747 | 110VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5748 | 110VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5749 | 110VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5750 | 110VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5751 | 110VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5752 | 110VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5753 | 110VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5754 | 110VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5755 | 110VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5756 | 110VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5757 | 110VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5758 | 110VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5759 | 110VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5760 | 110VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 7500W 150VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5763 | 150VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5764 | 150VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5765 | 150VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5766 | 150VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5767 | 150VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5768 | 150VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5769 | 150VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5770 | 150VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5771 | 150VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5772 | 150VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5773 | 150VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5774 | 150VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5775 | 150VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5776 | 150VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5777 | 150VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5778 | 150VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5779 | 150VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5780 | 150VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |

# 7500W 200VDC-250VDC

| 7500W 200VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5783 | 200VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5784 | 200VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5785 | 200VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5786 | 200VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5787 | 200VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5788 | 200VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5789 | 200VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5790 | 200VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5791 | 200VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5792 | 200VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5793 | 200VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5794 | 200VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5795 | 200VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5796 | 200VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5797 | 200VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5798 | 200VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5799 | 200VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5800 | 200VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 7500W 220VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5803 | 220VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5804 | 220VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5805 | 220VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5806 | 220VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5807 | 220VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5808 | 220VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5809 | 220VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5810 | 220VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5811 | 220VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5812 | 220VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5813 | 220VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5814 | 220VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5815 | 220VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5816 | 220VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5817 | 220VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5818 | 220VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5819 | 220VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5820 | 220VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 7500W 250VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5823 | 250VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5824 | 250VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5825 | 250VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5826 | 250VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5827 | 250VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5828 | 250VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5829 | 250VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5830 | 250VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5831 | 250VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5832 | 250VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5833 | 250VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5834 | 250VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5835 | 250VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5836 | 250VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5837 | 250VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5838 | 250VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5839 | 250VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5840 | 250VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |

# 7500W 280VDC-310VDC

| 7500W 280VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5843 | 280VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5844 | 280VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5845 | 280VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5846 | 280VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5847 | 280VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5848 | 280VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5849 | 280VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5850 | 280VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5851 | 280VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5852 | 280VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5853 | 280VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5854 | 280VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5855 | 280VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5856 | 280VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5857 | 280VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5858 | 280VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5859 | 280VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5860 | 280VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 7500W 300VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5863 | 300VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5864 | 300VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5865 | 300VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5866 | 300VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5867 | 300VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5868 | 300VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5869 | 300VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5870 | 300VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5871 | 300VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5872 | 300VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5873 | 300VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5874 | 300VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5875 | 300VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5876 | 300VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5877 | 300VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5878 | 300VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5879 | 300VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5880 | 300VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 7500W 310VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5883 | 310VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5884 | 310VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5885 | 310VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5886 | 310VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5887 | 310VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5888 | 310VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5889 | 310VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5890 | 310VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5891 | 310VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5892 | 310VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5893 | 310VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5894 | 310VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5895 | 310VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5896 | 310VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5897 | 310VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5898 | 310VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5899 | 310VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5900 | 310VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |

# 7500W 350VDC-450VDC

| 7500W 350VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5903 | 350VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5904 | 350VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5905 | 350VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5906 | 350VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5907 | 350VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5908 | 350VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5909 | 350VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5910 | 350VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5911 | 350VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5912 | 350VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5913 | 350VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5914 | 350VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5915 | 350VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5916 | 350VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5917 | 350VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5918 | 350VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5919 | 350VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5920 | 350VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 7500W 400VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5923 | 400VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5924 | 400VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5925 | 400VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5926 | 400VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5927 | 400VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5928 | 400VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5929 | 400VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5930 | 400VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5931 | 400VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5932 | 400VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5933 | 400VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5934 | 400VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5935 | 400VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5936 | 400VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5937 | 400VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5938 | 400VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5939 | 400VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5940 | 400VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 7500W 450VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5943 | 450VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5944 | 450VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5945 | 450VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5946 | 450VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5947 | 450VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5948 | 450VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5949 | 450VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5950 | 450VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5951 | 450VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5952 | 450VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5953 | 450VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5954 | 450VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5955 | 450VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5956 | 450VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5957 | 450VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5958 | 450VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5959 | 450VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5960 | 450VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |

| 7500W 500VDC INPUT ISOLATE DC DC CONVERTER | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Item No | Input voltage(VDC) | Output voltage(VDC) | Max output current(A) | Continuous current(A) | Max power(W) | Continuous power(W) | Size (MM) L*H*W | NW/GW (G) |
| 5963 | 500VDC±15% | 36VDC±1-2% | 208A | 166A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5964 | 500VDC±15% | 48VDC±1-2% | 156A | 125A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5965 | 500VDC±15% | 60VDC±1-2% | 125A | 100A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5966 | 500VDC±15% | 72VDC±1-2% | 104A | 83A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5967 | 500VDC±15% | 80VDC±1-2% | 93A | 75A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5968 | 500VDC±15% | 100VDC±1-2% | 70A | 60A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5969 | 500VDC±15% | 110VDC±1-2% | 68A | 54A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5970 | 500VDC±15% | 150VDC±1-2% | 50A | 40A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5971 | 500VDC±15% | 200VDC±1-2% | 37.5A | 30A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5972 | 500VDC±15% | 220VDC±1-2% | 34A | 27A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5973 | 500VDC±15% | 250VDC±1-2% | 30A | 24A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5974 | 500VDC±15% | 280VDC±1-2% | 26.7A | 21A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5975 | 500VDC±15% | 300VDC±1-2% | 25A | 20A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5976 | 500VDC±15% | 310VDC±1-2% | 24A | 19.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5977 | 500VDC±15% | 350VDC±1-2% | 21.4A | 17A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5978 | 500VDC±15% | 400VDC±1-2% | 18.7A | 15A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5979 | 500VDC±15% | 450VDC±1-2% | 16.6A | 13.3A | 7500W | 6000W | 440*350*130MM | 6/8KG |
| 5980 | 500VDC±15% | 500VDC±1-2% | 15A | 12A | 7500W | 6000W | 440*350*130MM | 6/8KG |